



FSP Hydro PTM PRO 1350W Power supply unit ATX ATXV3.1 Black

Brand : FSP

Product code: PPA13F0101

Product name : Hydro PTM PRO 1350W Power supply unit ATX ATXV3.1 Black

- Complies with ATX12V V3.0 & EPS12V V2.92
- Efficiency $\geq 92\%$ at typical load (1650W $\geq 94\%$ at typical load)
- Eco semi-fanless fan control switch
- Quiet and long-lasting 135mm FDB fan
- Ribbon cable design for enthusiasts
- +5V & 3.3V DC to DC module design
- +12V single-rail design
- Japanese electrolytic capacitors
- Changeable side stickers for DIY enthusiasts and gamers
- Complete protection: OCP/OVP/OPP/SCP/OTP/UVP

Hydro PTM PRO 1350W ATX3.0(12V-2x6)

FSP Hydro PTM PRO 1350W Power supply unit ATX ATXV3.1 Black. Total power: 1350 W, AC input voltage: 110 - 240 V, AC input frequency: 50/60 Hz. Motherboard power connector: 20+4 pin ATX, Cabling type: Fully-Modular. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Platinum. Product colour: Black, Cooling type: Semi-passive, Fan diameter: 13.5 cm. Width: 150 mm, Depth: 180 mm, Height: 86 mm



Power		Ports & interfaces	
Total power *	1350 W	Peripheral (Molex) power connectors (4-pin) *	4
AC input voltage *	110 - 240 V	PCI Express power connectors (6+2 pin)	4
AC input frequency	50/60 Hz	CPU power connector (4+4 pin)	✓
Power Factor Correction (PFC) type	Active	Cabling type	Fully-Modular
Number of +12V rail(s)	1	Performance	
Combined power (+3.3V)	20 W	80 PLUS certification *	80 PLUS Platinum
Combined power (+12V)	1350 W	Purpose *	PC
Combined power (+5V)	20 W	Power supply unit (PSU) form factor *	ATX
Combined power (-12V)	3.6 W	ATX version	3.0
Combined power (+5Vsb)	5 W	EPS version	2.92
Max output current (+3.3V)	20 A	Bearing technology	FDB
Max output current (+12V)	112.5 A	Design	
Max output current (+5V)	20 A	Product colour	Black
Max output current (-12V)	0.3 A	Cooling type	Semi-passive
Max output current (+5Vsb)	3 A	Fan diameter	13.5 cm
Efficiency	92%	Number of fans	1 fan(s)
Power protection features	Over current, Over power, Over voltage, Short circuit, Under voltage	On/off switch	✓
Ports & interfaces		Weight & dimensions	
Motherboard power connector *	20+4 pin ATX	Width	150 mm
Number of SATA power connectors	12	Depth	180 mm
		Height	86 mm



4713224529047

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.