



FSP VITA GM 850W White Power supply unit ATX ATX3.1 White

Brand : FSP

Product code: PPA8504214

Product name : VITA GM 850W White Power supply unit ATX ATX3.1 White

- Complies with ATX 12V V3.1 & EPS 12V V2.92
 - Efficiency $\geq 90\%$ at typical load
 - 80 PLUS ® gold certified
 - 105°C Japanese bulk capacitor
 - 120mm hydraulic bearing (HYB) fan
 - Fully modular cabling design
 - Complete protections: OVP, OCP, OPP, OTP, SCP, UVP, SIP, NLO 850W, ATX12V V3.1, 100-240V, 50/60Hz, 140×150×86 mm, White
- FSP VITA GM 850W White Power supply unit ATX ATX3.1 White. Total power: 850 W, AC input voltage: 100 - 240 V, AC input frequency: 50/60 Hz. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 60 cm, SATA power cable length: 500 mm. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Gold. Product colour: White, Cooling type: Active, Fan diameter: 12 cm. Cables included: CPU, Peripheral (Molex), SATA



Power		Ports & interfaces	
Total power *	850 W	PCI Express power connectors (6+2 pin)	4
AC input voltage *	100 - 240 V	CPU power connector (4+4 pin)	✓
AC input frequency	50/60 Hz	CPU power cable length	70 cm
Input current	11-5.5 A	Cabling type	Fully-Modular
Power Factor Correction (PFC) type	Active	Performance	
Combined power (+3.3V)	100 W	80 PLUS certification *	80 PLUS Gold
Combined power (+12V)	850 W	Purpose *	PC
Combined power (+5V)	100 W	Power supply unit (PSU) form factor *	ATX
Combined power (-12V)	3.6 W	ATX version	3.1
Combined power (+5Vsb)	15 W	EPS version	2.92
Max output current (+3.3V)	20 A	Bearing technology	HYB
Max output current (+12V)	70.83 A	Design	
Max output current (+5V)	20 A	Product colour	White
Max output current (-12V)	0.3 A	Cooling type	Active
Max output current (+5Vsb)	3 A	Fan diameter	12 cm
Efficiency	90%	Number of fans	1 fan(s)
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit, Surge & inrush protection (SIP), Under voltage	Fan location	Top
		Operational conditions	
Ports & interfaces		Operating temperature (T-T)	0 - 40 °C
Motherboard power connector *	20+4 pin ATX	Packaging content	
Motherboard power cable length	60 cm	Cables included	CPU, Peripheral (Molex), SATA
Number of SATA power connectors	8	Weight & dimensions	
SATA power cable length	500 mm	Width	150 mm
Peripheral (Molex) power connectors (4-pin) *	4	Depth	140 mm
		Height	86 mm



4713224529801

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.