

Zalman CNPS10X OPTIMAI, 120mm RGB PWM Fan / RGB Spectrum1,350 -2,100RPM uPWM / 18 -28.0dBA, Intel LGA 2066, 2011-V3 115x, 1200, 1366, AMD AM4, AM3+, AM3,, FM2+, FM2 Processor Cooler 12 cm White 1 pc(s)

Brand : Zalman

Product code: CNPS10X OPTIMAI
RGB


Product name : CNPS10X OPTIMAI, 120mm RGB PWM Fan / RGB Spectrum1,350 -2,100RPM uPWM / 18 -28.0dBA, Intel LGA 2066, 2011-V3 115x, 1200, 1366, AMD AM4, AM3+, AM3,, FM2+, FM2

- Easy Cable Connection
 - New Zalman-Inspired Design with Full Black Frame
 - Four Highly Conductive Copper Heatpipes
 - DTH(Direct Touch Heatpipes) Base
 - Compatible with LGA 1200
 - RGB fan
- CPU Cooler with RGB spectrum fan

Zalman CNPS10X OPTIMAI, 120mm RGB PWM Fan / RGB Spectrum1,350 -2,100RPM uPWM / 18 -28.0dBA, Intel LGA 2066, 2011-V3 115x, 1200, 1366, AMD AM4, AM3+, AM3,, FM2+, FM2 Processor Cooler 12 cm White 1 pc(s):

Quiet yet effective cooler with white housing

Zalman CNPS10X OPTIMAI, 120mm RGB PWM Fan / RGB Spectrum1,350 -2,100RPM uPWM / 18 -28.0dBA, Intel LGA 2066, 2011-V3 115x, 1200, 1366, AMD AM4, AM3+, AM3,, FM2+, FM2. Type: Cooler, Fan diameter: 12 cm, Rotational speed (min): 800 RPM, Rotational speed (max): 1200 RPM, Bearing type: Hydraulic. Width: 132 mm, Depth: 85 mm, Height: 158 mm. Product colour: White



Performance		Design	
Suitable location *	Processor	Material	Aluminium, Copper, Plastic
Type *	Cooler	Radiator material	Aluminum
Fan diameter	12 cm	Base plate material	Copper
Supported processor sockets	LGA 1150 (Socket H3), LGA 1151 (Socket H4), LGA 1155 (Socket H2), LGA 1156 (Socket H), LGA 1200 (Socket H5), LGA 1366 (Socket B), LGA 2011 (Socket R), LGA 2011-v3 (Socket R), LGA 2066, Socket AM3, Socket AM3+, Socket AM4, Socket FM2, Socket FM2+	Number of fans	1 fan(s)
		Number of heat pipes	4
		Illumination LED	✓
		Illumination colour	Blue, Green, Red
		Power	
Rotational speed (min)	800 RPM	Rated voltage	12 V
Rotational speed (max)	1200 RPM	Thermal Design Power (TDP)	180 W
Noise level (high speed)	27 dB	Weight & dimensions	
Maximum airflow	61.52 cfm	Width	132 mm
Pulse-width modulation (PWM) support	✓	Depth	85 mm
Bearing type	Hydraulic	Height	158 mm
Quantity per pack	1 pc(s)	Weight	740 g
Design			
Product colour *	White		



8809213769689

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 12-APR-2026. Prints or copies of Information are only valid on the printed Publication date