

Zalman ZM700-EBTII power supply unit 700 W 24-pin ATX ATX Black

Brand : Zalman

Product code: ZM700-EBTII

Product name : ZM700-EBTII

- 80 plus gold
 - Full modular
 - 99.9% Active PFC
- Zalman WattTera EBTII 700W power-supply

Zalman ZM700-EBTII power supply unit 700 W 24-pin ATX ATX Black:

High-Efficiency silent computer power supply
Zalman ZM700-EBTII. Total power: 700 W, AC input voltage: 100 - 240 V, AC input frequency: 50 - 60 Hz. Motherboard power connector: 24-pin ATX, Motherboard power cable length: 60 cm, SATA power cable length: 600 mm. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Gold. Product colour: Black, Cooling type: Active, Fan diameter: 13.5 cm. Certification: UL, FCC, KC, CE, CB, RoHS, EAC



Power		Ports & interfaces	
Total power *	700 W	PCI Express power cable length	55 cm
AC input voltage *	100 - 240 V	CPU power connector (4+4 pin)	✓
AC input frequency	50 - 60 Hz	CPU power cable length	55 cm
Input current	4.5 - 9 A	ATX Power connector (24-pin)	✓
Power factor	99.9	Floppy drive power connector	1
Power Factor Correction (PFC) type	Active	Cabling type	Fully-Modular
Combined power (+12V)	696 W	Performance	
Combined power (-12V)	3.6 W	80 PLUS certification *	80 PLUS Gold
Combined power (+5Vsb)	15 W	Purpose *	PC
Max output current (+3.3V)	20 A	Power supply unit (PSU) form factor *	ATX
Max output current (+12V)	58 A	ATX version	2.31
Max output current (+5V)	20 A	Silent mode	✓
Max output current (-12V)	0.3 A	Bearing technology	Ball bearing
Max output current (+5Vsb)	3 A	Mean time between failures (MTBF)	100000 h
Efficiency	91%	Design	
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage	Product colour	Black
Ports & interfaces		Cooling type	Active
Motherboard power connector *	24-pin ATX	Fan diameter	13.5 cm
Motherboard power cable length	60 cm	Number of fans	1 fan(s)
Number of SATA power connectors	8	Fan speed	1000 - 1900 RPM
SATA power cable length	600 mm	Fan location	Top
Peripheral (Molex) power connectors (4-pin) *	3	On/off switch	✓
Peripheral (Molex) power cable length	600 mm	Operational conditions	
EPS power connector (8-pin)	✓	Operating temperature (T-T)	0 - 40 °C
EPS power connector (4+4 pin)	✓	Certificates	
		Certification	UL, FCC, KC, CE, CB, RoHS, EAC

Ports & interfaces		Weight & dimensions	
PCI Express power connectors (6+2 pin)	5	Width	150 mm
		Depth	160 mm
		Height	86 mm
		Weight	3.08 kg



8809213769283

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 12-APR-2026. Prints or copies of Information are only valid on the printed Publication date