


## Viewsonic 75" 4K Professional Commercial Display with ProAV Integration

**Brand :** Viewsonic

**Product code:** CDE7531-1C


**Product name :** 75" 4K Professional Commercial Display with ProAV Integration



- Fast Warm Boot eliminates long startup delays, launching signage and content in under 7 seconds.
  - Native 4K UHD in Any Orientation delivers sharp, high-resolution visuals in landscape or portrait.
  - USB media playback & scheduling with automatic failover ensures uninterrupted signage
  - Commercial-Grade Brightness & 24/7 Reliability keep content clear and visible around the clock.
  - Centralized control with Pro-AV integration and remote management via Web UI and ViewSonic Manager.
  - Secure, Future-Ready Platform with Android 14, upgradeable OS, Quad-Core SoC, and 8 GB RAM.
- 75", 4K UHD (3840 x 2160), TFT LCD, DLED, 500 nits, 5000:1, 6.5 ms, Quad-core ARM Cortex-A73, 8GB, 32GB, 2x 16 W, HDMI 2.0/2.1, RS-232, WIFI slot, SPDIF, RJ45, USB-A, USB-C, 3.5 mm, Android 14 AOSP

| Display                                         |                           | Design                        |                  |
|-------------------------------------------------|---------------------------|-------------------------------|------------------|
| Panel type                                      | TFT                       | Bezel width (side)            | 1.59 cm          |
| LED backlight                                   | ✓                         | Bezel width (top)             | 1.59 cm          |
| LED backlighting type                           | Direct-LED                | Anti-glare screen             | ✓                |
| Display diagonal *                              | 190.5 cm (75")            | Performance                   |                  |
| Display technology *                            | LCD                       | Purpose *                     | Commercial       |
| Display resolution *                            | 3840 x 2160 pixels        | Operating hours (hours/days)  | 24/7             |
| Display brightness *                            | 500 cd/m²                 | Power                         |                  |
| HD type *                                       | 4K Ultra HD               | Power consumption (typical) * | 89.19 W          |
| Touchscreen *                                   | ✗                         | Energy efficiency class (SDR) | F                |
| Native aspect ratio                             | 16:9                      | AC input voltage              | 100 - 240 V      |
| Response time                                   | 6.5 ms                    | Computer system               |                  |
| Contrast ratio (typical)                        | 1200:1                    | Built-in processor *          | ✓                |
| Contrast ratio (dynamic)                        | 5000:1                    | Processor manufacturer        | ARM              |
| Viewing angle, horizontal                       | 178°                      | Processor architecture        | ARM Cortex-A73   |
| Viewing angle, vertical                         | 178°                      | Processor cores               | 4                |
| Active display area (W x H)                     | 1650.24 x 928.26 mm       | Internal memory               | 8 GB             |
| Panel life                                      | 50000 h                   | Internal storage capacity     | 32 GB            |
| Native refresh rate                             | 60 Hz                     | Operating system installed    | Android 14       |
| Haze rate                                       | 25%                       | Weight & dimensions           |                  |
| Surface hardness                                | 3H                        | Display width                 | 1685.6 mm        |
| Ports & interfaces                              |                           | Display depth                 | 68 mm            |
| HDMI ports quantity *                           | 4                         | Display height                | 963.7 mm         |
| HDMI version                                    | 2.0/2.1                   | Display weight                | 34.1 kg          |
| HDMI input ports quantity                       | 3                         | Weight                        | 34.1 kg          |
| HDMI output ports quantity                      | 1                         | Packaging data                |                  |
| DVI port *                                      | ✗                         | Package width                 | 1863 mm          |
| DisplayPort version                             | 1.2                       | Package depth                 | 225 mm           |
| USB port *                                      | ✓                         | Package height                | 1090 mm          |
| USB ports quantity                              | 3                         | Package weight                | 48.4 kg          |
| USB version                                     | 2.0/3.2 Gen 1 (3.1 Gen 1) | Packaging content             |                  |
| USB connector type                              | USB Type-A, USB Type-C    | Remote control included       | ✓                |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity | 1                         | Batteries included            | ✓                |
| USB Power Delivery (USB PD)                     | ✓                         | Cables included               | AC, HDMI, RS-232 |
| USB Power Delivery up to                        | 65 W                      | Mounting kit                  | ✓                |
| USB Type-C DisplayPort Alternate Mode           | ✓                         | Operational conditions        |                  |
| Ethernet LAN (RJ-45) ports                      | 2                         | Operating temperature (T-T)   | 0 - 40 °C        |
| PC Audio in                                     | ✓                         |                               |                  |

| Ports & interfaces          |                            | Operational conditions            |                                  |
|-----------------------------|----------------------------|-----------------------------------|----------------------------------|
| RS-232 interface            | ✓                          | Operating relative humidity (H-H) | 20 - 80%                         |
| Digital audio optical out   | 1                          | Logistics data                    |                                  |
| PC Audio out                | ✓                          | Products per master (outer) case  | 1 pc(s)                          |
| OPS module slot             | ✓                          | Pallet gross length               | 114 cm                           |
| Audio                       |                            | Pallet gross width                | 195 cm                           |
| Built-in speaker(s) *       | ✓                          | Pallet gross height               | 122 cm                           |
| Number of built-in speakers | 2                          | Harmonized System (HS) code       | 8528521000                       |
| RMS rated power             | 32 W                       | Network                           |                                  |
| Design                      |                            | Ethernet LAN *                    | ✓                                |
| Product design *            | Digital signage flat panel | Ethernet LAN data rates           | 10,100,1000 Mbit/s               |
| Placement supported *       | Indoor                     | Wi-Fi *                           | ✓                                |
| Orientation                 | Horizontal/Vertical        | Technical details                 |                                  |
| Product colour *            | Black                      | OPS slot                          | 1                                |
| Screen shape                | Flat                       | Sustainability certificates       | ENERGY STAR, EPEAT Gold, ErP     |
| VESA mounting *             | ✓                          | Compliance certificates           | CB, CE, EAC, Federal             |
| Panel mounting interface    | 600 x 400 mm               |                                   | Communications Commission (FCC), |
| Bezel width (bottom)        | 1.59 cm                    | Other features                    |                                  |
|                             |                            | Bundled software                  | AirSync, Manager                 |



766907034738

## **Catalog Object Cloud**