



TP-Link EAP668 Outdoor HD 3500 Mbit/s White Power over Ethernet (PoE)

Brand : TP-Link

Product code: EAP668-OUTDOOR HD

Product name : EAP668 Outdoor HD

- Ultra-Fast 3.6 Gbps Wi-Fi 6 Speeds: 1148 Mbps on 2.4 GHz and 2402 Mbps on 5 GHz.
 - High-Density Connectivity: Supports up to 1,024 devices.
 - Multiple Ports for Flexible Network Solutions: 1× 10G SFP+ slot, 1× 2.5G PoE-In port, and 1× Gigabit PoE-Out port.
 - PoE+/PoE++ Powered and PoE+ Out: Supports 802.3at/bt PoE input and 802.3at PoE output.
 - Ideal for Outdoor Environments: IP68-rated weatherproof enclosure, 6 kV lightning protection, and a reliable operating range of -40 °C to +70 °C.
 - Advanced Features: Omada Mesh, Seamless Roaming, Bluetooth, and Centralized Cloud Management.
- EAP668-Outdoor HD AX3600 Indoor/Outdoor WiFi 6 Access Point
- TP-Link EAP668 Outdoor HD. 2.4 GHz, 5 GHz, Maximum data transfer rate: 3500 Mbit/s. Security algorithms: WPA-Enterprise, WPA-Personal, WPA2-Enterprise, WPA2-Personal, WPA3-Enterprise, WPA3-Personal. Power over Ethernet (PoE). Product colour: White



Features		Design	
2.4 GHz *	✓	Placement *	Pole
5 GHz *	✓	Product colour *	White
6 GHz *	✗	Reset button	✓
Maximum data transfer rate *	3500 Mbit/s	Antenna	
Maximum data transfer rate (2.4 GHz)	1148 Mbit/s	Antenna type *	External
Maximum data transfer rate (5 GHz)	2402 Mbit/s	Antenna direction type	Omni-directional
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11k, IEEE 802.11n, IEEE 802.11r, IEEE 802.11v	Antennas quantity	4
		Antenna gain level (max)	6 dBi
Bluetooth	✓	Certificates	
Security		Certification	CE, FCC, RoHS
Security algorithms *	WPA-Enterprise, WPA-Personal, WPA2-Enterprise, WPA2-Personal, WPA3-Enterprise, WPA3-Personal	Weight & dimensions	
Protocols		Width	240 mm
DHCP client	✓	Depth	80 mm
Management features		Height	315 mm
Web-based management	✓	Packaging content	
Cloud-managed	✓	Quantity per pack	1 pc(s)
Firmware upgradeable	✓	Mounting kit	✓
Ports & interfaces		Operational conditions	
Ethernet LAN (RJ-45) ports *	3	Operating relative humidity (H-H)	10 - 90%
Power		Operating temperature (T-T)	-40 - 70 °C
Power over Ethernet (PoE) *	✓	Storage temperature (T-T)	-40 - 70 °C
		Storage relative humidity (H-H)	5 - 90%



1210002602570



1210002602587

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.