



HP 772 300-ml Magenta DesignJet Ink Cartridge

Brand : HP

Product code: CN629A

Product name : 772 300-ml Magenta DesignJet Ink Cartridge



- Ideal for low-volume print service providers, including copy shops and quick printers.
 - Ink cartridge
- 772 300-ml Magenta DesignJet Ink Cartridge

HP 772 300-ml Magenta DesignJet Ink Cartridge:

Ideal for low-volume print service providers, including copy shops and quick printers. HP 772 300-ml Magenta DesignJet Ink Cartridges print with the same vivid colour and the same professional quality, over and over again. Original HP supplies are designed together with the printer to provide consistent, trouble-free printing. HP 772 300-ml Magenta DesignJet Ink Cartridge. Compatibility: HP Designjet Z5200 PostScript Printer, Print technology: Thermal inkjet, Printing colours: Magenta. Width: 283 mm, Depth: 41 mm, Height: 118 mm. Package width: 283 mm, Package depth: 41 mm, Package height: 118 mm. Master (outer) cases per pallet: 102 pc(s), Layers per pallet: 6 pc(s), Pallet gross weight: 297 kg. Pallet dimensions (W x D x H): 1200 x 1000 x 920 mm



Performance		Logistics data	
Compatibility *	HP Designjet Z5200 PostScript Printer	Master (outer) cases per pallet	102 pc(s)
Print technology	Thermal inkjet	Pallet dimensions (W x D x H)	1200 x 1000 x 920 mm
Printing colours	Magenta	Layers per pallet	6 pc(s)
Country of origin	Singapore	Pallet gross weight	297 kg
Weight & dimensions		Master (outer) case gross weight	2.72 kg
Width	283 mm	Quantity per pack	1 pc(s)
Depth	41 mm	Technical details	
Height	118 mm	Box contents	Ink cartridge
Weight	440 g	Total carbon footprint (kg of CO2e)	0.8
Packaging data		Other EU Hazard statement(s)	EUH208: Contains sensitizing substance. May produce an allergic reaction
Package width	283 mm	Master (outer) cases per pallet layer	17 pc(s)
Package depth	41 mm	Other features	
Package height	118 mm	UNSPSC-code	44103105
Package weight	500 g		
Operational conditions			
Operating temperature (T-T)	15 - 35 °C		
Operating relative humidity (H-H)	20 - 80%		
Storage temperature (T-T)	15 - 35 °C		



8849626389968



0884962638996



884962638996

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-APR-2026. Prints or copies of Information are only valid on the printed Publication date