



DELL P Series P2421 computer monitor 61.2 cm (24.1") 1920 x 1200 pixels WUXGA LCD Black

Brand : DELL

Product family: P Series

Product code: DELL-P2421

Product name : P2421

- 61.2cm (24.1") WUXGA 1920 x 1200 LED IPS
- 8ms, 16:10, 300cd/m², 1000:1
- USB, VGA, DVI, HDMI, DisplayPort
61.2cm (24.1") WUXGA 1920 x 1200 LED IPS, 16:10, 300cd/m², 16.78M, 8ms, 178°/178°, 1000:1

DELL P Series P2421 computer monitor 61.2 cm (24.1") 1920 x 1200 pixels WUXGA LCD Black:

See more and scroll less with 11% more screen real estate on a tall 24", 16:10 WUXGA monitor.
DELL P Series P2421. Display diagonal: 61.2 cm (24.1"), Display resolution: 1920 x 1200 pixels, HD type: WUXGA, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:10, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub, USB hub version: 2.0 / 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black



Display		Ergonomics	
Display diagonal *	61.2 cm (24.1")	Tilt adjustment	✓
Display resolution *	1920 x 1200 pixels	Tilt angle range	-5 - 21°
HD type *	WUXGA	Power	
Native aspect ratio *	16:10	Energy efficiency class (SDR) *	D
Display technology *	LCD	Energy consumption (SDR) per 1000 hours *	15 kWh
Panel type *	IPS	Power consumption (typical) *	14.8 W
Backlight type	LED	Power consumption (standby) *	0.2 W
Touchscreen *	✗	Power consumption (max)	42 W
Display brightness (typical)	300 cd/m²	Power consumption (off)	0.2 W
Response time *	8 ms	AC input voltage	120 - 230 V
Screen shape *	Flat	AC input frequency	50 - 60 Hz
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1600 x 1200 (UXGA), 1920 x 1200 (WUXGA)	Power supply type	Internal
Supported video modes	480i, 480p, 576i, 576p, 720p, 1080i, 1080p	Energy efficiency scale	A to G
Contrast ratio (typical) *	1000:1	Operational conditions	
Maximum refresh rate *	60 Hz	Operating temperature (T-T)	0 - 40 °C
Viewing angle, horizontal	178°	Storage temperature (T-T)	-20 - 60 °C
Viewing angle, vertical	178°	Operating relative humidity (H-H)	20 - 80%
Display number of colours *	16.7 million colours	Storage relative humidity (H-H)	10 - 90%
Response time (fast)	5 ms	Operating altitude	0 - 5000 m
Pixel pitch	0.27 x 0.27 mm	Non-operating altitude	5000 - 12192 m
Pixel density	94 ppi	Weight & dimensions	
Horizontal scan range	30 - 83 kHz	Width (with stand)	531 mm
Vertical scan range	56 - 76 Hz	Depth (with stand)	166 mm
Viewable size, horizontal	51.8 cm	Height (with stand)	500.8 mm
Viewable size, vertical	32.4 cm	Weight (with stand)	5.1 kg
		Width (without stand)	531 mm
		Depth (without stand)	44.1 mm

Display		Weight & dimensions	
Viewable size diagonal	61.1 cm	Height (without stand)	349.5 mm
High Dynamic Range (HDR) supported	✗	Weight (without stand)	3.5 kg
Colour gamut standard	sRGB	Bezel width (side)	6.3 mm
sRGB coverage (typical)	99%	Bezel width (top)	6.3 mm
		Bezel width (bottom)	1.92 cm
Multimedia		Packaging data	
Built-in speaker(s) *	✗	Package width	167 mm
Built-in camera *	✗	Package depth	608 mm
		Package height	420 mm
		Package weight	7.3 kg
Design		Packaging content	
Market positioning *	Business	Stand included	✓
Product colour *	Black	Cables included	AC, DVI, DisplayPort, USB Type-C to USB Type-C, VGA
Ports & interfaces		Sustainability	
Built-in USB hub *	✓	Sustainability certificates	ENERGY STAR
USB hub version	2.0 / 3.2 Gen 1 (3.1 Gen 1)		
Number of upstream ports	1	Carbon footprint	
USB Type-A downstream ports quantity	4	Total carbon footprint (kg of CO2e)	475
VGA (D-Sub) ports quantity	1	Total carbon emissions, standard deviation (kg of CO2e)	96
DVI port	✓	Carbon emissions, manufacturing (kg of CO2e)	329.96
HDMI *	✓	Carbon emissions, logistics (kg of CO2e)	38.2
HDMI ports quantity	1	Carbon emissions, energy usage (kg of CO2e)	105
HDMI version	1.4	Carbon emissions, end-of-life (kg of CO2e)	2.19
DisplayPorts quantity	1	PAIA version	1.2.6, 2020
DisplayPort version	1.2		
Audio input	✗	Other features	
Headphone out *	✗	Compliance certificates	RoHS
Network		Logistics data	
Wi-Fi	✗	Harmonized System (HS) code	85285210
Ergonomics			
VESA mounting *	✓		
Panel mounting interface	100 x 100 mm		
Cable lock slot *	✓		
Height adjustment *	✓		
Adjustable height (max)	13 cm		
Pivot	✓		
Pivot angle	-90 - 90°		
Swivelling	✓		
Swivel angle range	-45 - 45°		



5397184200773



5704174468745

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.