

Epson TM-T70II (032) 180 x 180 DPI Wired Thermal POS printer

Brand : Epson

Product code: C31CD38032

Product name : TM-T70II (032)



TM-T70II (032) - SERIAL + BUILT-IN USB, PS, EDG, EU

Epson TM-T70II (032). Print technology: Thermal, Type: POS printer, Maximum resolution: 180 x 180 DPI. Maximum roll diameter: 8.3 cm, Supported paper width: 80 mm. Connectivity technology: Wired, USB connector: USB Type-B, Standard interfaces: Serial. Sound pressure level (printing): 55 dB, Mean time between failures (MTBF): 360000 h, Country of origin: China. Product colour: Black

Printing		Operational conditions	
Maximum resolution	180 x 180 DPI	Operating relative humidity (H-H)	10 - 90%
Print speed	250 mm/sec	Storage relative humidity (H-H)	10 - 90%
Print technology *	Thermal	Weight & dimensions	
Type *	POS printer	Width	125 mm
Paper handling		Depth	194 mm
Maximum roll diameter	8.3 cm	Height	114 mm
Supported paper width	80 mm	Weight	1.7 kg
Ports & interfaces		Packaging data	
USB port *	✓	Cables included	AC
USB 2.0 ports quantity	1	Quantity per pack	1 pc(s)
USB connector	USB Type-B	Package width	192 mm
Serial interface *	✓	Package depth	253 mm
Bluetooth	✗	Package height	240 mm
Connectivity technology *	Wired	Package weight	2.56 kg
Serial ports quantity	1	Print technology	
Standard interfaces	Serial	Column capacity	80 mm, 56 / 42
Network		Logistics data	
Ethernet LAN *	✗	Harmonized System (HS) code	84433210
Wi-Fi *	✗	Products per pallet	112 pc(s)
Features		Products per pallet layer	16 pc(s)
Sound pressure level (printing)	55 dB	Pallet gross width	80 cm
Mean time between failures (MTBF)	360000 h	Pallet gross length	120 cm
Country of origin	China	Pallet gross height	181.6 cm
Safety	TÜV, GOST-R	Products per pallet (UK)	168 pc(s)
Certification	CE, EN55022 Class A	Products per pallet layer (UK)	24 pc(s)
Design		Pallet width (UK)	100 cm
Product colour *	Black	Pallet length (UK)	120 cm
Power		Pallet height (UK)	181.6 cm
Power consumption	100 mA	Other features	
Operational conditions		Dimensions (WxDxH)	125 x 194 x 114 mm
Operating temperature (T-T)	5 - 40 °C	Buffer size	4 KB
Storage temperature (T-T)	-10 - 50 °C		



5054484562894



8715946530611

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.