



Canon VB-M641V Dome IP security camera Indoor 1280 x 960 pixels

Brand : Canon

Product code: 0309C001

Product name : VB-M641V

IP, Indoor, 1/3" CMOS, 1.3 MP, f=2.55 - 6.12 mm, PTZ, 2.4 Optical Zoom, Day/Night, 1 x Fast Ethernet RJ-45, 2-Way Audio, microSD/microSDHC/microSDX, PoE

[Canon VB-M641V Dome IP security camera Indoor 1280 x 960 pixels:](#)

Compact, fully featured, vandal-resistant indoor fixed dome with enhanced low light performance.

Keep every angle covered

- High quality images day or night with 1.3 MP resolution
- Superb low light performance and ultra wide coverage
- Quick and easy installation with simple connections
- Additional Intelligent Intruder and Scream detection
- Enhanced bandwidth management and bit rate control

Canon VB-M641V. Type: IP security camera, Placement supported: Indoor, Connectivity technology: Wired. Product colour: White, Form factor: Dome, Protection features: Vandal proof. Minimum illumination: 0.001 lx, Angle of rotation: 350°, Lens viewing angle, horizontal: 111.5°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.9 mm (1 / 2.9"). Optical zoom: 2.4x, Digital zoom: 4x, Focal length range: 2.55 - 6.12 mm

Performance		Audio	
Type *	IP security camera	Audio system full duplex	✓
Placement supported *	Indoor	Audio detection	✓
Connectivity technology *	Wired	Network	
PTZ control	✓	Ethernet LAN *	✓
Day/night mode	✓	IPv4: TCP/IP, UDP, HTTP, FTP, SNMP (MIB2), SMTP (Client), DHCP (Client), DNS (Client), mDNS, ARP, ICMP, POP3 (Client), NTP (Client), SMTP authentication (POP before SMTP, SMTP-AUTH), AutoIP, RTP/RTCP, RTSP, SSL/TLS, IPsec, WV-HTTP (Canon proprietary), ONVIF (Profile S, Profile G) IPv6: TCP/IP, UDP, HTTP, FTP, SMTP (Client), DHCPv6 (Client), DNS (Client), mDNS, ICMPv6, POP3 (Client), NTP (Client), SMTP authentication (POP before SMTP, SMTP-AUTH), RTP/RTCP, RTSP, SSL/TLS, IPsec, WV-HTTP (Canon proprietary), ONVIF (Profile S, Profile G)	
Processor model	Canon DIGIC DV III		
Light exposure modes	Auto, Manual, Shutter priority AE		
Design			
Form factor *	Dome		
Product colour *	White		
Protection features	Vandal proof		
Camera			
Minimum illumination	0.001 lx		
Angle of rotation	350°		
Lens viewing angle, horizontal	111.5°		
Tilt angle range	-75 - 75°		
Tilt speed	20.7 °/sec		
Pan range	-175 - 175°		
Pan speed	20.1 °/sec		
White balance	Mercury lamp, Auto, Fluorescent, Halogen, Manual	Supported network protocols	
Camera shutter speed	0.0000625 - 1 s	Wi-Fi *	✗
Image sensor		Cabling technology	10/100Base-T(X)
Optical sensor size	25.4 / 2.9 mm (1 / 2.9")	Storage	
Progressive scan	✓	Built-in HDD *	✗
Sensor type *	CMOS	Card reader integrated	✓
Lens system		Compatible memory cards	MicroSD (TransFlash), MicroSDHC, MicroSDXC
Zoom capability	✓	Ports & interfaces	
Optical zoom	2.4x	Ethernet LAN (RJ-45) ports	1
Digital zoom	4x	Microphone in	✓
		Security	
		Video motion detection	✓



Lens system		Security	
Focal length range	2.55 - 6.12 mm	Security algorithms	802.1x RADIUS, EAP-MD5, EAP-PEAP, EAP-TLS, EAP-TTLS, SSL/TLS
Focus adjustment	1.2 - 1.8	Management features	
Night vision		Web-based management	✓
Night vision *	✗	Power	
Video		Power source type *	PoE
Maximum resolution *	1280 x 960 pixels	AC input voltage	100-240 V
Total megapixels *	1.3 MP	Power consumption (max)	9.8 W
Video formats supported	H.264	Power over Ethernet (PoE)	✓
Supported graphics resolutions	320 x 180, 320 x 240, 640 x 360, 1280 x 960, 1280 x 720 (HD 720), 640 x 480 (VGA)	Operational conditions	
Frame rate	30 fps	Operating temperature (T-T)	-10 - 50 °C
Full HD	✗	Operating relative humidity (H-H)	5 - 85%
Audio		System requirements	
Audio system	2-way	Windows operating systems supported	✓
		Weight & dimensions	
		Width	150 mm
		Depth	150 mm
		Height	129 mm
		Weight	910 g
		Packaging content	
		AC adapter included	✗
		Bundled software	Camera Management Tool Camera Angle Setting Tool RM-Lite Proxy Authentication Admin Tools/Admin Viewer
		Other features	
		Compliance industry standards	IEEE802.3at PoE+
		Technical details	
		Power source	AC, DC, PoE



4549292032505

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.