



## InLine USB Display AOC Cable, USB-C male to HDMI male (DP Alt Mode), 50m

**Brand :** InLine

**Product code:** 64250A

**Product name :** InLine USB Display AOC Cable, USB-C male to HDMI male (DP Alt Mode), 50m

InLine USB Display AOC Cable, USB-C male to HDMI male (DP Alt Mode), 50m

[InLine USB Display AOC Cable, USB-C male to HDMI male \(DP Alt Mode\), 50m:](#)

USB 3.2 Type-C male to HDMI 2.0b A male hybrid cable, hybrid active optical cable (AOC) USB 3.2 Gen.2, bandwidth 10Gb/s

USB Type-C: DisplayPort Alternate Mode, DP1.2 support

Supports computer resolutions to 4K@60Hz

Input: USB Type-C male (video source)

Output: HDMI A male (display)

Plug and Play - no drivers needed

Gold plated contacts

Metal connector: Zinc alloy housing - sturdy and robust

AOC Cable: Converts electrical data signals to optical signals

4 cores multimode fiber (high speed data) & 7 cores copper (power and low speed data)

Round cable black PVC jacket, OD: 5.2mm

Supports resolutions up to UHD 3840×2160@60Hz / 4096×2160@60Hz

Supports HDR10, 3D, CEC

Self-detecting function for EDID information

Operation temperature: 0°C-+50°C

Storage temperature: -20°C-+70°C



| Features                              |                          | Features                            |                               |
|---------------------------------------|--------------------------|-------------------------------------|-------------------------------|
| Connector 1 form factor               | Straight                 | High Dynamic Range (HDR) technology | High Dynamic Range 10 (HDR10) |
| Connector 2 form factor               | Straight                 | <b>Operational conditions</b>       |                               |
| Cable length *                        | 50 m                     | Operating temperature (T-T)         | 0 - 50 °C                     |
| Connector 1 *                         | USB Type-C               | Storage temperature (T-T)           | -20 - 70 °C                   |
| Connector 2 *                         | HDMI                     | <b>Weight &amp; dimensions</b>      |                               |
| Connector 1 gender *                  | Male                     | Cable diameter                      | 5.2 mm                        |
| Connector 2 gender *                  | Male                     | Weight                              | 1.32 kg                       |
| HDMI version                          | 2.0b                     | Width                               | 20 mm                         |
| DisplayPort version                   | 1.2                      | Depth                               | 50000 mm                      |
| USB Type-C DisplayPort Alternate Mode | ✓                        | Height                              | 10 mm                         |
| Maximum resolution                    | 4096 x 2160 pixels       | <b>Packaging data</b>               |                               |
| Supported graphics resolutions        | 4096 x 2160              | Package width                       | 210 mm                        |
| Refresh rate at maximum resolution    | 60 Hz                    | Package depth                       | 215 mm                        |
| 3D                                    | ✓                        | Package height                      | 80 mm                         |
| Product colour                        | Black                    | Package weight                      | 1.5 kg                        |
| Jacket material                       | Polyvinyl chloride (PVC) | Package type                        | Box                           |
| Connector material                    | Gold                     | <b>Packaging content</b>            |                               |
| Plug and Play                         | ✓                        | Quantity per pack                   | 1 pc(s)                       |
|                                       |                          | <b>Other features</b>               |                               |
|                                       |                          | Dimensions (WxDxH)                  | 20 x 50000 x 10 mm            |



4043718304035

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.