



InLine 66659E network media converter 10000 Mbit/s 850 nm Multi-mode Black

Brand : InLine

Product code: 66659E

Product name : 66659E

- Efficient media converter for easy network migration from copper to fiber
- Supports 10 Gb/s transmission rate for high network performance
- Link Fault Pass Through (LFP) function for easy maintenance
- Low power consumption and stable performance over long periods of time
- Plug-and-play solution for easy installation

Network Media Converter 10Gb/s TP to SFP+ fiber optic (for LC Duplex)

InLine 66659E. Maximum data transfer rate: 10000 Mbit/s, Converter input interface: 10Base-T, 10GBase-T, 100Base-T, 1000Base-T, Converter output interface: 10GBASE-R. Maximum transfer distance: 300 m, Wavelength: 850 nm, Fiber mode structure: Multi-mode. LED indicators: Status, Product colour: Black. Fiber optic connector: LCD, SFP+, Connectivity technology: Wired. Output voltage: 12 V, Output current: 1 A



Network		Weight & dimensions	
Maximum data transfer rate *	10000 Mbit/s	Width	94 mm
Converter input interface	10Base-T, 10GBase-T, 100Base-T, 1000Base-T	Depth	110 mm
Converter output interface	10GBASE-R	Height	26 mm
Networking standards	IEEE 802.3x	Weight	290 g
Ethernet interface type	2.5 Gigabit Ethernet, 5 Gigabit Ethernet, 10 Gigabit Ethernet, Fast Ethernet, Gigabit Ethernet	Operational conditions	
Ethernet LAN data rates	10,100,1000,2500,5000,10000 Mbit/s	Operating temperature (T-T)	0 - 55 °C
Link Fault Pass-through (LFP)	✓	Storage temperature (T-T)	-40 - 80 °C
Performance		Operating relative humidity (H-H)	5 - 80%
Maximum transfer distance *	300 m	Packaging content	
Wavelength *	850 nm	AC adapter included	✓
Fiber mode structure	Multi-mode	Manual	✓
Features		Packaging data	
Internal *	✗	Package width	124 mm
LED indicators	Status	Package depth	230 mm
Product colour	Black	Package height	52 mm
Ports & interfaces		Package volume	1400 cm³
Connectivity technology	Wired	Package weight	388 g
Ethernet LAN (RJ-45) ports	1	Package type	Box
Fiber ports quantity	1	Certificates	
Fiber optic connector *	LCD, SFP+	Compliance certificates	TÜV mark
Power		Logistics data	
Output voltage	12 V	Country of origin	Taiwan
Output current	1 A	Other features	
		Dimensions (WxDxH)	94 x 110 x 26 mm



4043718338047

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.