



InLine 76660V interface cards/adapters Internal M.2



Brand : InLine

Product code: 76660V

Product name : 76660V

InLine PCI Express card to 1x internal NVMe M.2 Key M, PCIe x4

InLine 76660V. Host interface: PCIe, Output interface: M.2, Host interface gender: Male. Country of origin: Taiwan. Data transfer rate (max): 4 Gbit/s, Bandwidth: 32 Gbit/s. Power supply input voltage: 3.3 V. Windows operating systems supported: Windows 10, Windows 11, Windows 8, Windows 8.1, Linux operating systems supported: Kernel 2.6.31, Kernel 2.6.33, Kernel 3.12, Kernel 3.17, Kernel 3.3, Kernel 4.6.4, Linux Kernel..., Server operating systems supported: Windows Server 2012 R2



Ports & interfaces		System requirements	
Host interface *	PCIe	Windows operating systems supported	Windows 10, Windows 11, Windows 8, Windows 8.1
Host interface gender	Male		Kernel 2.6.31, Kernel 2.6.33, Kernel 3.12, Kernel 3.17, Kernel 3.3, Kernel 4.6.4, Linux Kernel 5.10, Linux Kernel 5.11, Linux Kernel 5.12, Linux Kernel 5.13, Linux Kernel 5.14, Linux Kernel 5.15, Linux Kernel 5.19, Linux Kernel 5.4, Linux Kernel 5.8, Linux Kernel 5.9, Linux Kernel 6.2, Linux Kernel 6.5
Output interface *	M.2	Linux operating systems supported	Linux Kernel 5.13, Linux Kernel 5.14, Linux Kernel 5.15, Linux Kernel 5.19, Linux Kernel 5.4, Linux Kernel 5.8, Linux Kernel 5.9, Linux Kernel 6.2, Linux Kernel 6.5
Expansion card standard	PCIe 3.0		Linux Kernel 5.13, Linux Kernel 5.14, Linux Kernel 5.15, Linux Kernel 5.19, Linux Kernel 5.4, Linux Kernel 5.8, Linux Kernel 5.9, Linux Kernel 6.2, Linux Kernel 6.5
NVMe	✓	Server operating systems supported	Windows Server 2012 R2
Number of M.2 (M) slots	1		Windows Server 2012 R2
Design		Technical details	
Internal *	✓	Compliance certificates	TÜV mark, Federal Communications Commission (FCC), CE
LED indicators	✓		
Country of origin	Taiwan	Weight & dimensions	
Features		Width	95 mm
Data transfer rate (max)	4 Gbit/s	Depth	52 mm
Bandwidth	32 Gbit/s	Weight	33 g
Power		Packaging data	
Power supply input voltage	3.3 V	Mounting brackets included	✓
Operational conditions		Manual	✓
Operating temperature (T-T)	-40 - 85 °C	Package weight	33 g
		Package type	Hanging box



4043718341603

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.