



FSP VITA GM 1000W White Power supply unit ATX ATX3.1 White

Brand : FSP

Product code: PPA10A4013

Product name : VITA GM 1000W White Power supply unit
ATX ATX3.1 White

- Complies with ATX 12V V3.1 & EPS 12V V2.92
- Efficiency $\geq$ 90% at typical load
- 80 PLUS [®] gold certified
- 105°C Japanese bulk capacitor
- 120mm hydraulic bearing (HYB) fan
- Fully modular cabling design
- Complete protections: OVP, OCP, OPP, OTP, SCP, UVP, SIP, NLO

VITA GM 1000W White

FSP VITA GM 1000W White Power supply unit ATX ATX3.1 White. Total power: 1000 W, AC input voltage: 100 - 240 V, AC input frequency: 50/60 Hz. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 60 cm, SATA power cable length: 500,810,965,655 mm. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Gold. Product colour: White, Cooling type: Active, Fan diameter: 12 cm. Cables included: CPU, PCIe, Peripheral (Molex), SATA



Power		Ports & interfaces	
Total power *	1000 W	Peripheral (Molex) power cable length	810,965 mm
AC input voltage *	100 - 240 V	PCI Express power connectors (6+2 pin)	4
AC input frequency	50/60 Hz	PCI Express power connectors (12+4 pin)	1
Input current	12 - 6 A	CPU power connector (4+4 pin)	✓
Power factor	0.9	CPU power cable length	70 cm
Power Factor Correction (PFC) type	Active	PCI Express connector	✓
Combined power (+3.3V)	100 W	Cabling type	Fully-Modular
Combined power (+12V)	1000 W	Performance	
Combined power (+5V)	100 W	80 PLUS certification *	80 PLUS Gold
Combined power (-12V)	3.6 W	Purpose *	PC
Combined power (+5Vsb)	15 W	Power supply unit (PSU) form factor *	ATX
Max output current (+3.3V)	20 A	ATX version	3.1
Max output current (+12V)	83.33 A	EPS version	2.92
Max output current (+5V)	20 A	Bearing technology	Hydraulic
Max output current (-12V)	0.3 A	Design	
Max output current (+5Vsb)	3 A	Product colour	White
Efficiency	90%	Cooling type	Active
Power protection features	No load operation, Over current, Over power, Over total voltage, Over voltage, Short circuit, Surge & inrush protection (SIP), Under voltage	Fan diameter	12 cm
		Number of fans	1 fan(s)
Ports & interfaces		Fan location	Top
Motherboard power connector *	20+4 pin ATX	On/off switch	✓
Motherboard power cable length	60 cm	Packaging content	
Number of SATA power connectors	6	Cables included	CPU, PCIe, Peripheral (Molex), SATA
SATA power cable length	500,810,965,655 mm		
Number of SATA power cables	2		
Peripheral (Molex) power connectors (4-pin) *	2		

Weight & dimensions

Width	150 mm
Depth	140 mm
Height	86 mm



4713224529818



4713224529788

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.