

TP-Link InSight S385DPS Bullet IP security camera Outdoor 5456 x 1520 pixels Wall



Brand : TP-Link

Product code: INSIGHT S385DPS

Product name : InSight S385DPS

- 4K (8MP) Ultra-High Definition
- Dual-lens Stitched Panoramic Imaging
- Ultra-Low Light ColorPro Night Vision
- Red-Blue Warning Lights and Sound Alerts
- People & Vehicle Analytics†
- Human & Vehicle Classification
- Smart Detection
- Smart Video Enhancement Technology
- Audio and Alarm Interface Available
- IP67 Weatherproof and IK10 Vandal-Proof
- H.265+ Compression Technology

4K (8MP), 5456×1520, 1/3 to 1/10000 s, Fixed Focal Lens, Two-Way Audio, IP67, IK10, Metal, 266 × 116 × 90 mm, 1.12 kg

TP-Link InSight S385DPS. Type: IP security camera, Placement supported: Outdoor, Connectivity technology: Wired. Mounting type: Wall, Product colour: White, Form factor: Bullet. Lens viewing angle, horizontal: 180°, Lens viewing angle, vertical: 51°, Lens viewing angle, diagonal: 180°. Sensor type: CMOS, Optical sensor size: 25.4 / 1.79 mm (1 / 1.79"). Sensor type (panoramic camera): CMOS

Performance		Audio	
Type *	IP security camera	Audio formats supported	G.711 A-law
Placement supported *	Outdoor	Sample rate	8 kHz
Connectivity technology *	Wired	Built-in microphone	✓
Maximum operating distance	76 m	Number of microphones	1
Wide Dynamic Range (WDR)	✓	Bit rate range	0 - 64 Kbit/s
Day/night mode	✓	Network	
Infrared (IR) cut-off filter	✓	Ethernet LAN *	✓
Remote viewing	✓	Networking standards	IEEE 802.3at
Dynamic range	120 dB	Supported network protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS, FTP/SFTP, RTP, IPv4, IPv6, ARP
Design		Wi-Fi *	✗
Form factor *	Bullet	Bluetooth *	✗
Mounting type *	Wall	SIM card slot	✓
Product colour *	White	SIM card type	MicroSIM
Housing material	Metal	Live view	✓
Protection features	Waterproof	Storage	
International Protection (IP) code	IP67	Compatible memory cards	MicroSD (TransFlash)
IK code	IK10	Maximum memory card size	512 GB
Weatherproof	✓	Ports & interfaces	
Camera		Ethernet LAN (RJ-45) ports	1
Minimum illumination	0 lx	DC-in jack	✓
Lens viewing angle, horizontal	180°	Security	
Lens viewing angle, vertical	51°	Built-in siren	✓
Lens viewing angle, diagonal	180°	Password protection	✓
Tilt angle range	0 - 90°	Video motion detection	✓
Camera shutter speed	1/3 to 1/10000	IP address filtering	✓
Image sensor		HTTPS encryption	✓
Optical sensor size	25.4 / 1.79 mm (1 / 1.79")	Alert notification type	Push notification
Progressive scan	✓	Motion sensor	✓
Sensor type *	CMOS		
Panoramic camera			
Sensor type (panoramic camera)	CMOS		

Lens system		Security	
Detect distance	76 m	Mirror	✓
Observe distance	29 m	Human and vehicle targets classification	✓
Recognize distance	14 m	Digest authentication	✓
Fixed focus	✓	Management features	
Fixed focal length	5 mm	Web-based management	✓
Night vision		Web browser	✓
Night vision *	✓	Cloud-managed *	✓
LED type	IR/White	Reset button	✓
Video		Power	
Maximum resolution *	5456 x 1520 pixels	Power source type *	DC, PoE
Total megapixels *	8 MP	Power consumption (max)	18 W
Video compression formats	H.264, H.264+, H.265, H.265+	Power consumption (Power over Ethernet (PoE))	21 W
Video recording	✓	DC output voltage	12
Image quality adjustment	Brightness, Contrast, Mirror, Saturation, Sharpness	Operational conditions	
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)	Operating temperature (T-T)	-30 - 60 °C
Bit rate	Main Stream: 256 Kbps to 8 Mbps, Sub-Stream: 64 Kbps to 1024 Kbps	Storage temperature (T-T)	-40 - 60 °C
Back Light Compensation (BLC)	✓	Operating relative humidity (H-H)	0 - 95%
Highlight Compensation (HLC)	✓	Storage relative humidity (H-H)	0 - 95%
Digital Wide Dynamic Range (DWDR)	✓	Weight & dimensions	
Audio		Width	116 mm
Built-in speaker(s)	✓	Height	90 mm
Audio system	2-way	Length	266 mm
Audio input channels	1.0 channels	Weight	1.12 kg
Audio output channels	1.0 channels	Packaging content	
		Number of cameras *	1
		Mounting kit	✓
		Screws included	✓
		Drilling template included	✓
		Manual	✓



8885020627824

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.