



Lenovo 94Y5180 network card Internal Ethernet / Fiber 10000 Mbit/s

Brand : Lenovo

Product code: 94Y5180

Product name : 94Y5180



Broadcom NetXtreme Dual Port 10GbE SFP+ Adapter

[Lenovo 94Y5180 network card Internal Ethernet / Fiber 10000 Mbit/s:](#)

Virtualization, cloud computing, high performance computing (HPC), and clustering initiatives are increasing workload demands. The Broadcom network adapter family is the solution of choice for workload-intensive computing environments, providing a reliable, high-performance 10 GbE connectivity solution.

These adapters support PCI-SIG single root input/output virtualization (SR-IOV) and NIC partitioning (NPAR). SR-IOV delivers higher performance and lower CPU utilization with increased virtual machine (VM) scalability.

QLogic NPAR enables up to four physical, switch-agnostic, switch-independent NIC partitions per adapter port. Dynamic and fine-grained bandwidth provisioning enables control of network traffic from VMs and hypervisor services.

Lenovo 94Y5180. Internal. Connectivity technology: Wired, Host interface: PCI Express, Interface: Ethernet / Fiber. Maximum data transfer rate: 10000 Mbit/s. Product colour: Green

Ports & interfaces		Design	
Connectivity technology *	Wired	Certification	EN55022 EN55024 EN60950 / CE EN 61000-3-2 EN 61000-3-3 ICES-003, Issue-004 IEC 950 CB Scheme FCC 47 CFR Part 15 Class A UL 1950 CSA C22.2 950-95 VCCI AS/NZSCISPR 22 / C-tick RRL for KC BSMI UL 94-/V
Host interface *	PCI Express		
Interface *	Ethernet / Fiber		
Fiber ports quantity	2		
Fiber optic connector	SFP+		
PCI version	2.0		
Network		System requirements	
Maximum data transfer rate *	10000 Mbit/s	Linux operating systems supported	Red Hat Enterprise Linux WS 5.0, SuSE Linux 11
Networking standards *	IEEE 802.1p, IEEE 802.3ae, IEEE 802.3x	Other operating systems supported	VMware vSphere ESXi
Ethernet interface type	10 Gigabit Ethernet	Server operating systems supported	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2
Ethernet LAN data rates	10,100,1000,10000 Mbit/s		
Jumbo frames support	✓	Operational conditions	
Design	Green	Operating temperature (T-T)	0 - 55 °C
		Storage temperature (T-T)	-20 - 65 °C
		Weight & dimensions	
Product colour	Green	Width	17 mm
Internal *	✓	Depth	168 mm
		Height	69 mm
		Logistics data	
		Harmonized System (HS) code	85176990



0883436501439



883436501439

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.