

CyberPower CP1000EIPFCRM1U uninterruptible power supply (UPS) Line-Interactive 1000 kVA 600 W 6 AC outlet(s)



Brand : CyberPower

Product code: CP1000EIPFCRM1U

Product name : CP1000EIPFCRM1U

CyberPower CP1000EIPFCRM1U. UPS topology: Line-Interactive, Output power capacity: 1000 kVA, Output power: 600 W. AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 6 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Typical backup time at full load: 2.2 min, Typical backup time at half load: 10.5 min. Form factor: Rackmount, Product colour: Black, Silver, Housing material: Metal. Compliance certificates: CE, RoHS

Features		Battery	
UPS topology *	Line-Interactive	Battery recharge time	8 h
Output power capacity *	1000 kVA	Hot-swap battery	✓
Output power *	600 W	Rechargeable battery	✓
Waveform *	Pure sine	Design	
Input operation voltage (min) *	165 V	Form factor *	Rackmount
Input operation voltage (max) *	271 V	Housing material	Metal
Input frequency *	50/60 Hz	Cable length	1.83 m
Output frequency	50/60 Hz	Product colour *	Black, Silver
Output frequency regulation	3 Hz	Display type	LCD
Automatic Voltage Regulation (AVR)	✓	LED indicators	✓
Maximum current	10 A	Operational conditions	
Surge energy rating	450 J	Operating temperature (T-T)	0 - 40 °C
Response time	7 ms	Storage temperature (T-T)	-15 - 45 °C
Heat dissipation	18.4 BTU/h	Operating relative humidity (H-H)	0 - 95%
Number of input phases	1	Storage relative humidity (H-H)	0 - 95%
Number of output phases	1	Operating altitude	0 - 3000 m
Power factor	0.6	Non-operating altitude	0 - 15000 m
Power Factor Correction (PFC) type	Active	Certificates	
Surge protection	✓	Compliance certificates	CE, RoHS
Audible alarm(s)	✓	Packaging content	
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm	Quick installation guide	✓
Power source type	AC	Sustainability	
Socket circuit breaker	✓	Sustainability compliance	✓
Ports & interfaces		Weight & dimensions	
AC outlet types	C13 coupler	Width	433 mm
Power plug	C14 coupler	Depth	388.7 mm
AC outlets quantity	6 AC outlet(s)	Height	44 mm
Serial interface	✓	Weight	13.4 kg
Serial ports quantity	1	Packaging data	
Ethernet LAN (RJ-45) ports	2	Package width	530 mm
Battery		Package depth	494 mm
Battery technology	Sealed Lead Acid (VRLA)	Package height	158 mm
Typical backup time at full load	2.2 min	Package weight	15.5 kg
Typical backup time at half load	10.5 min	Other features	
		Battery type	RBP0025
		Nominal output voltage	230 V
		Nominal input voltage	220-240 V

Other features

Overload protection





4711027798028

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.