



APC Easy UPS On-Line uninterruptible power supply (UPS) Double-conversion (Online) 3 kVA 2700 W 6 AC outlet(s)

Brand : APC

Product code: SRVL3KRIRK

Product name : Easy UPS On-Line

- Replacement battery (1) is available
- 3kVA/2.7kW double-conversion on-line pure sine wave 2U rackmount UPS
- Rack/Tower convertible (rail kit included)
- Lithium-ion battery minimizes the need to replace battery during UPS lifetime
- Graceful shutdown of servers and workstations

Easy UPS On-Line, 3kVA, Lithium-ion, Rack/Tower 2U, 230V, 6 IEC C13 + 1 IEC C19 outlets, Intelligent Card Slot, W/ rail kit

APC Easy UPS On-Line. UPS topology: Double-conversion (Online), Output power capacity: 3 kVA, Output power: 2700 W. AC outlet types: C13 coupler, C19 coupler, Power plug: C20 coupler, AC outlets quantity: 6 AC outlet(s). Battery technology: Lithium-Ion (Li-Ion), Battery voltage: 48 V, Typical backup time at full load: 9 min. Form factor: Rackmount/Tower, Product colour: Black, Rack capacity: 2U. Compliance certificates: CE, RoHS, UKCA, Certification: CB CE UKCA UN 38.3 IEC 62619


Features		Battery	
UPS topology *	Double-conversion (Online)	Typical backup time at full load	9 min
Output power capacity *	3 kVA	Battery life (max)	10 year(s)
Output power *	2700 W	Battery recharge time	1.5 h
Waveform *	Sine	Design	
Input operation voltage (min) *	110 V	Form factor *	Rackmount/Tower
Input operation voltage (max) *	300 V	Rack capacity	2U
Input frequency *	40 - 70 Hz	Cooling type	Active
Output operation voltage (max)	230 V	Built-in fan	✓
Output frequency	50/60 Hz	Product colour *	Black
Surge energy rating	945 J	Control type	Buttons
Heat dissipation	1024 BTU/h	Display type	LCD
Efficiency	90%	LED indicators	✓
Crest factor	3:1	International Protection (IP) code	IP20
ECO mode	✓	Operational conditions	
Emergency Power Off (EPO)	✓	Storage temperature (T-T)	-20 - 50 °C
Noise level	50 dB	Operating relative humidity (H-H)	0 - 95%
Audible alarm(s)	✓	Storage relative humidity (H-H)	0 - 95%
Audible alarm modes	Low battery alarm, Overload alarm	Operating altitude	0 - 3000 m
Power source type	AC	Non-operating altitude	0 - 15000 m
Detachable power cord	✓	Certificates	
Ports & interfaces		Compliance certificates	CE, RoHS, UKCA
AC outlet types	C13 coupler, C19 coupler	Certification	CB CE UKCA UN 38.3 IEC 62619
Power plug	C20 coupler	Packaging content	
AC outlets quantity	6 AC outlet(s)	Rack mount kit	✓
USB port	✓	Cables included	Output power cable, Phone (RJ-11), RJ-45, RS-232, USB cable
USB port type	USB Type-B	Weight & dimensions	
Serial interface	✓	Width	438 mm
Serial interface type	RS-232	Depth	632 mm
RS-232 ports	1	Height	86 mm
Modem (RJ-11) ports	1	Weight	21.2 kg
Ethernet LAN (RJ-45) ports	1	Packaging data	
Emergency Power Off (EPO) connector	✓	Package width	600 mm
Battery		Package depth	800 mm
Battery technology	Lithium-Ion (Li-Ion)	Package height	240 mm
Battery voltage	48 V		

Packaging data

Package weight	29.1 kg
----------------	---------



0731304621904



731304621904

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.