

Ochno O-SWO-100-S-1

Brand : Ochno

Product code: O-SWO-100-S-1

Product name : O-SWO-100-S-1

- Socket surface: black
 - 18mm drilling hole
 - 1m USB-C and I/O cable
 - With LED button
 - USB-C lock screw
 - USB 3.2 Gen 2 (3.1 Gen 2)
 - DisplayPort Alt mode 1.4
 - Charging 100W, PD 3.1
 - Used together with O-SBC-200-1 for I/O control
 - RoHS/REACH
- O-SWO-100-S-1



Ochno O-SWO-100-S-1:

USB-C socket with LED button for integration into any table surface. With the button the user can easily select between BYOD/MTR/charging modes. For a user friendly experience in any meeting space.

Connected via USB-C to Power Conference hub.

Ochno O-SWO-100-S-1. Socket type: Type C, USB version: USB 3.2 Gen 2 (3.1 Gen 2), Maximum data transfer rate: 10000 Mbit/s. Product colour: Black, Cable jacket material: Thermoplastic elastomer (TPE), LED indicators: Status. USB output voltage: 20 V, USB output current: 5 A, Input current: 5 A. Hole diameter: 1.8 cm, Weight: 73 g. Quantity per pack: 1 pc(s), Package width: 100 mm, Package depth: 100 mm

Features		Power	
Socket type *	Type C	Input current	5 A
Sockets quantity *	1	Input voltage	20 V
USB version	USB 3.2 Gen 2 (3.1 Gen 2)	Technical details	
Maximum data transfer rate	10000 Mbit/s	Compliance certificates	CE, RoHS, REACH
Installation type	Desktop embedded	Packaging content	
Mounting type	Desk	Quick start guide	✓
Connector 1 gender	Male	Safety sheet	✓
Connector 2 gender	Female	Weight & dimensions	
Connector 1 form factor	Straight	Hole diameter	1.8 cm
Connector 2 form factor	Straight	Weight	73 g
Connector contacts plating	Gold	Packaging data	
DisplayPort (Alt mode)	✓	Quantity per pack	1 pc(s)
DisplayPort version	1.4	Package width	100 mm
Design		Package depth	100 mm
Product colour *	Black	Package height	32 mm
Cable jacket material	Thermoplastic elastomer (TPE)	Package weight	98 g
Frame	✓	Package type	Box
LED indicators	Status	Logistics data	
Cable length	1 m	Master (outer) case width	210 mm
Locking screw	✓	Master (outer) case length	355 mm
Power		Master (outer) case height	110 mm
USB output voltage	20 V	Master (outer) case gross weight	2 kg
USB output current	5 A	Products per master (outer) case	18 pc(s)
USB Power Delivery (USB PD)	✓		



7350113051325

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.