



Microconnect MC-POEADAPTER-22W-USB-C PoE adapter Fast Ethernet 20 V

Brand : Microconnect

Product code: MC-POEADAPTER-22W-USB-C


Product name : MC-POEADAPTER-22W-USB-C



22W PoE Adapter RJ45 IEEE802.3af to USB-C

Microconnect MC-POEADAPTER-22W-USB-C PoE adapter Fast Ethernet 20 V:

MC-POEADAPTER22W-USB-C is a network power adapter designed based on the IEEE802.3af standard. The output is a standard Type-C interface, which can provide 5V/2.6A 9V/1.75A 12V/1.45A 15V/1.37A 20V/1.15A power supply and 100Mbps Internet data transmission. MC-POEADAPTER22W-USB-C is designed with a small volume white plastic case, which is convenient since it can be carried around on the desktop or can be fixed and opened for use. The input and output of the device do not exceed the safe voltage of 57V, and there is no need for electric shock protection. The product has passed the EU CE certification. The device needs to be used in a wired network environment that supports IEEE802.3af, plug and play without configuration, and the output supports PD3.0 fast charging protocol, which can provide continuous power supply and stable network connection to low-power mobile devices such as mobile phones, game consoles, and tablet computers.



Network		Power	
Ethernet interface type	Fast Ethernet	Output power	60 W
Ethernet LAN data rates	100 Mbit/s	Input voltage	44-57 V
Cabling technology	10/100	Output current	3 A
Power over Ethernet (PoE)	✓	Certificates	
Networking standards	IEEE 802.3af	Compliance certificates	CE
Cable types supported	Cat5	Sustainability	
Features		Sustainability compliance	✓
Product colour	White	Operational conditions	
Housing material	Plastic	Operating temperature (T-T)	-20 - 40 °C
Easy to install	✓	Operating relative humidity (H-H)	20 - 80%
USB Power Delivery (USB PD)	✓	Storage temperature (T-T)	-20 - 70 °C
USB Power Delivery revision	3.0	Storage relative humidity (H-H)	10 - 90%
Fast charging	✓	Operating altitude	0 - 2000 m
Maximum operating distance	100 m	Weight & dimensions	
LED indicators	✓	Width	51 mm
International Protection (IP) code	IP40	Depth	18.5 mm
Ports & interfaces		Height	91 mm
RJ-45 input ports	1	Weight	63 g
USB Type-C ports quantity	1	Packaging data	
Power		Package weight	70 g
Power over Ethernet (PoE) voltage *	20 V	Logistics data	
		Country of origin	China



5704174977414

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.