


Microconnect B-UTP605W networking cable White 5 m Cat6 U/UTP (UTP)



Brand : Microconnect

Product code: B-UTP605W

Product name : B-UTP605W

- To order a full box, please select the following quantity: 40 pcs.
 - Suitable for Gigabit (10/100/1000 Mbit) network
 - CAT6 tested up to 250 MHz
 - with Latch Protection
 - with slimline relief
 - with gold-plated pins
- CAT6 U/UTP Network Cable 5m, White

Microconnect B-UTP605W networking cable White 5 m Cat6 U/UTP (UTP):

CAT6 cables enables a convenient and reliable connection from one network device, such as switch, modem or router, to another or to the infrastructure at large through a patch panel, keystone jack or wall outlet. This cable are also used a lot in small office and home network and entertainment applications. These cables are tested up to 250Mhz (CAT6 standard) and are backwards compatible with CAT5e and CAT5 cables. They are produced with latch protection, which prevents the connector do be damaged when you install the cable through an installation with very less space.

Microconnect B-UTP605W. Cable length: 5 m, Cable standard: Cat6, Cable shielding: U/UTP (UTP), Connector 1: RJ-45, Connector 2: RJ-45, Data transfer rate: 10000 Mbit/s, Product colour: White

Features		Operational conditions	
Product colour *	White	Storage relative humidity (H-H)	10 - 90%
Cable length *	5 m	Certificates	
Cable standard *	Cat6	Compliance certificates	RoHS
Cable shielding *	U/UTP (UTP)	Weight & dimensions	
Connector 1 *	RJ-45	Outer diameter	6 mm
Connector 2 *	RJ-45	Weight	28 g
Connector 1 gender *	Male	Packaging content	
Connector 2 gender *	Male	Quantity per pack	1 pc(s)
Jacket material	Polyvinyl chloride (PVC)	Packaging data	
Conductor type	Stranded	Package width	148 mm
Conductor material	Copper-Clad Aluminium (CCA)	Package depth	143 mm
AWG wire size	26/7	Package height	44 mm
Data transfer rate	10000 Mbit/s	Package weight	128 g
Frequency	250 MHz	Logistics data	
Operational conditions		Harmonized System (HS) code	84733080
Operating temperature (T-T)	0 - 70 °C	Other features	
Storage temperature (T-T)	-40 - 85 °C	Technical features	Kink Protection, strain relief and Latch Protection
Operating relative humidity (H-H)	10 - 85%		



4040849686375

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.