

Fujifilm X -T5 MILC Body 40.2 MP X-Trans CMOS 5 HR 7728 x 5152 pixels Black



Brand : Fujifilm

Product family: X

Product code: 4181407

Product name : X-T5

40.2 MPix, 23.5mm x 15.7mm (APS-C) X-Trans CMOS 5 HR, Ultra Sonic Vibration, X-Processor 5, 6.2K 6240 x 3510, 3" Touch LCD, 0.5 OLED VF, WLAN, Bluetooth, USB-Type C, HDMI Micro D, EU Bundle Fujifilm X -T5. Camera type: MILC Body, Megapixel (approx.): 40.2 MP, Sensor type: X-Trans CMOS 5 HR, Maximum image resolution: 7728 x 5152 pixels. ISO sensitivity (max): 51200. Fastest camera shutter speed: 1/180000 s. Wi-Fi. HD type: 6.2K, Maximum video resolution: 6240 x 3510 pixels. Display diagonal: 7.62 cm (3"), Touchscreen. Viewfinder type: Electronic. Weight: 476 g. Product colour: Black

Picture quality		Viewfinder	
Image sensor aspect ratio	3:2	Viewfinder eyepoint (approx.)	2.4 cm
Camera type *	MILC Body	Viewfinder technology	OLED
Megapixel (approx.) *	40.2 MP	Viewfinder resolution (approx.)	3690000 pixels
Sensor type *	X-Trans CMOS 5 HR	Ports & interfaces	
Sensor cleaning system	Ultrasonic vibration	USB version *	3.2 Gen 2 (3.1 Gen 2)
Maximum image resolution *	7728 x 5152 pixels	USB connector	USB Type-C
Still image resolution(s) *	6864 x 5152, 7728 x 5152, 7728 x 4344, 5152 x 5152, 6432 x 5152, 4864 x 3648, 5472 x 3648, 5472 x 3080, 3648 x 3648, 4560 x 3648, 3456 x 2592, 3888 x 2592, 3888 x 2184, 2592 x 2592, 3264x2592, 9600 x 2160, 9600 x 1440, 6400 x 2160, 6400 x 1440	HDMI *	✓
		HDMI connector type	Micro
		Microphone in	✓
		Headphone outputs	1
		Headphone connectivity	3.5 mm
Image stabilizer *	✓	Network	
Image stabilizer location	Camera body	Bluetooth *	✓
Supported aspect ratios	1:1, 3:2, 4:3, 5:4, 16:9	Bluetooth version	4.2
Image sensor size (W x H)	23.5 x 15.7 mm	Wi-Fi *	✓
Sensor format	Advanced Photo System type-C (APS-C)	Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
Image formats supported *	HEIF, JPEG, Raw, TIFF	Camera	
Lens system		White balance *	Daylight, Fluorescent H, Fluorescent L, Incandescent, Shade, Underwater
Lens mount interface	Fujifilm X	Scene modes *	Panorama
Focusing		Shooting modes *	Auto, Manual, Program
Focus *	TTL	Photo effects *	Black&White, Sepia, Vivid
Focus adjustment *	Auto/Manual	Self-timer delay *	2,3,5,10 s
Auto focusing (AF) modes *	Continuous Auto Focus, Single Auto Focus	Contrast adjustment	✓
Exposure		Dioptre correction	✓
ISO sensitivity (min) *	64	Start-up time	490 ms
ISO sensitivity (max) *	51200	High Dynamic Range (HDR) supported	✓
ISO sensitivity	64, 80, 100, 125, 25600, 51200	Tripod mounting supported *	✓
Light exposure modes *	Aperture priority AE, Auto, Manual, Shutter priority AE	Built-in processor	✓
Light exposure correction *	± 5EV (1/3EV step)	Image processor	X-Processor 5

Exposure		Design	
Light metering *	Centre-weighted, Evaluative (Multi-pattern), Spot	Product colour *	Black
Shutter		Battery	
Fastest camera shutter speed *	1/180000 s	Battery technology *	Lithium-Ion (Li-Ion)
Slowest camera shutter speed *	3600 s	Battery type	NP-W235
Camera shutter type	Electronic, Mechanical	Number of batteries supported	1
Video		Power	
Video recording *	✓	USB Type-C charging port *	✓
		Operational conditions	
Maximum video resolution *	6240 x 3510 pixels	Operating temperature (T-T)	-10 - 40 °C
HD type *	6.2K	Operating relative humidity (H-H)	10 - 80%
Video resolutions	1920 x 1080, 2048 x 1080, 3840 x 2160, 4096 x 2160	Weight & dimensions	
Video formats supported	HEVC, MOV, MP4	Width	129.5 mm
Memory		Depth	63.8 mm
Compatible memory cards *	SD, SDHC, SDXC	Height	91 mm
Memory slots	1	Weight	476 g
Maximum memory card size	2 TB	Weight (including battery)	557 g
Display		Packaging content	
Display *	LCD	Shoulder strap	✓
Touchscreen *	✓	AC adapter included *	✓
Display diagonal *	7.62 cm (3")	Cables included	USB
Display resolution	1840000 dot	Batteries included	✓
Display aspect ratio	3:2		
Viewfinder			
Viewfinder type	Electronic		
Magnification	0.8x		
Viewfinder screen size	0.5"		



4547410553048

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.