

Logitech R500 Laser Presentation Remote

Brand : Logitech

Product code: 910-006520

Product name : R500 Laser Presentation Remote

R500 Laser Presentation Remote

Logitech R500 Laser Presentation Remote. Wireless receiver interface: USB, Wireless technology: Bluetooth/RF, Receiver type: Nano receiver. Product colour: Grey, Presenter functions: Laser pointer, Remote control, Laser pointer colour: Red. Battery technology: Alkaline, Battery capacity: 1000 mAh, Battery type: AAA. Mac operating systems supported: Yes, MacOS, Minimum system requirements: Logitech proprietary receiver: - USB port - Windows 10 or later, Windows 8, Windows 7 -.... Receiver width: 1.75 cm, Receiver depth: 2.5 cm, Receiver height: 6.6 mm



Performance		System requirements	
Wireless receiver interface *	USB	Minimum system requirements	Logitech proprietary receiver: – USB port – Windows 10 or later, Windows 8, Windows 7 – macOS X 10.12 or later – Chrome OS – Linux 2.6+ Bluetooth connection: – Bluetooth – Windows 10 or later, Windows 8 – iOS 8 or later – Android 5.0 or later – Internet connection for software download
Receiver type	Nano receiver		
Wireless technology *	Bluetooth/RF		
Bluetooth Low Energy (BLE)	✔		
Frequency band	2.4 GHz		
Wireless range	20 m		
Features		Weight & dimensions	
Product colour *	Grey	Receiver width	1.75 cm
Presenter functions *	Laser pointer, Remote control	Receiver depth	2.5 cm
Buttons quantity *	3	Receiver height	6.6 mm
Laser pointer colour	Red	Receiver weight	2 g
Laser class	1	Width	36.6 mm
Laser wave power	0.039 mW	Depth	123.6 mm
Wavelength range	640 - 660 nm	Height	24.7 mm
Power		Weight	48.4 g
Number of batteries supported	1	Packaging data	
Battery technology	Alkaline	Quantity per pack	1 pc(s)
Battery capacity	1000 mAh	Package weight	100 kg
Battery type	AAA	Package width	36.5 mm
Battery life	12 month(s)	Package depth	90.5 mm
System requirements		Package height	248 mm
Windows operating systems supported	✔	Package weight	115 g
Mac operating systems supported	Yes, MacOS	Packaging content	
Linux operating systems supported	✔	Batteries included	✔
		Receiver included	✔
		User guide	✔
		Packaging content	Presentation remote USB Dongle 1 AAA Battery User documentation

Logistics data

Master (outer) case width	98.5 mm
Master (outer) case length	302 mm
Master (outer) case height	262 mm
Master (outer) case gross weight	1.02 kg



5099206100589

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-APR-2026. Prints or copies of Information are only valid on the printed Publication date