

Brother HL-L3240CDW laser printer Colour 600 x 2400 DPI A4 Wi-Fi

Brand : Brother

Product code: HL-L3240CDW

Product name : HL-L3240CDW

- Print up to 26 pages per minute
 - 2-Sided print, up to 10 sides per minute
 - Gigabit ethernet, 5GHz WiFi and USB
 - 250 Sheet paper input capacity¹¹
 - User-friendly 1 line LCD control panel
 - 1,000 Page yield inbox toner, 3,000 page mono 2,300 page colour high yield available⁸
- This device utilises new LED technology to quietly produce high-quality colour documents without sacrificing speed. Smarter printing. Greater savings with FREE EcoPro Trial.

Brother HL-L3240CDW laser printer Colour 600 x 2400 DPI A4 Wi-Fi:

The office and home environment is continuously changing with the goal of increasing efficiency and productivity. Be confident that you have a reliable device that prints quickly and effortlessly, with:

- 2-Sided print, up to 10 sides per minute
- 1 Line LCD control panel
- Gigabit ethernet, 5GHz WiFi and USB
- 256MB Internal memory
- 250 Sheet paper input tray¹¹
- Comes with 1,000 black, 1,000 colour page yield toners, 3,000 black, 2,300 colour maximum yield available⁸
- 2 month FREE trial to EcoPro



Printing		Performance	
Duplex printing mode	Auto	Internal memory *	256 MB
Print speed (colour, normal quality, A4/US Letter)	26 ppm	Sound pressure level (printing)	47 dB
Colour *	✓	Design	
Print technology *	LED	Market positioning *	Home & office
Duplex printing *	✓	Product colour *	White
Maximum resolution *	600 x 2400 DPI	Built-in display *	✓
Print speed (black, normal quality, A4/US Letter) *	26 ppm	Display	LCD
Warm-up time	28 s	Power	
Time to first page (black, normal)	13.5 s	Power consumption (printing) *	520 W
Features		Power consumption (max)	960 W
Maximum duty cycle *	3000 pages per month	Power consumption (ready)	70 W
Printing colours *	Black, Cyan, Magenta, Yellow	Power consumption (off)	0.04 W
Page description languages *	BR-Script 3, PCL 5c, PCL 5e, PCL 6, PDF 1.7	Energy Star Typical Electricity Consumption (TEC)	0.4 kWh/week
Country of origin	Vietnam	AC input voltage	220 - 240 V
Input & output capacity		AC input frequency	50/60 Hz
Total number of input trays *	1	Operational conditions	
Total input capacity *	250 sheets	Operating temperature (T-T)	10 - 32 °C
Total output capacity *	150 sheets	Storage temperature (T-T)	0 - 40 °C
Paper handling		Operating relative humidity (H-H)	20 - 80%
Maximum ISO A-series paper size *	A4	Storage relative humidity (H-H)	35 - 85%
Paper tray media types *	Bond paper, Envelopes, Labels, Plain paper, Recycled paper, Thick paper, Thicker paper, Thin paper	Weight & dimensions	
ISO A-series sizes (A0...A9) *	A4, A5, A6	Width	488 mm
ISO B-series sizes (B0...B9)	B5	Depth	370 mm
Non-ISO print media sizes	Executive, Legal, Letter	Height	488 mm
		Weight	15.5 kg

Paper handling		Packaging data	
JIS B-series sizes (B0...B9)	B5, B6	Package width	488 mm
Envelopes sizes	C5, Com-10, DL, Monarch	Package depth	488 mm
Paper tray media weight	60 - 163 g/m ²	Package height	370 mm
Ports & interfaces		Package weight	18 kg
Direct printing *	✓	Logistics data	
USB port *	✓	Pallet gross height	16.3 cm
USB 2.0 ports quantity	1	Pallet gross weight	306.5 kg
Network		Master (outer) cases per pallet	16 pc(s)
Wi-Fi *	✓	Layers per pallet	4 pc(s)
Ethernet LAN *	✓	Products per pallet	16 pc(s)
Cabling technology	10/100/1000Base-T(X)	Technical details	
Ethernet LAN data rates	10,100,1000 Mbit/s	Master (outer) cases per pallet layer	4 pc(s)
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n)	Pallet type	1200 x 1000 mm
Security algorithms	WPA2-AES, 64-bit WEP, WPA2-PSK, 128-bit WEP, WPA3-SAE, WPA-AES, WPA-PSK, WPA-TKIP	Other features	
Supported network protocols (IPv4)	ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), WINS/ NetBIOS name resolution, DNS Resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/ Port9100, SMTP Client, IPP/IPPS, FTP Client and Server, CIFS Client, TELNET Server, SNMPv1/v2c/v3, HTTP/HTTPS server, TFTP client and server, ICMP, Web Services (Print/Scan), SNMP Client, Syslog	Warranty period	2 year(s)
Supported network protocols (IPv6)	NDP, RA, DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port9100, IPP/IPPS, SMTP Client, FTP Client and Server, CIFS Client, TELNET Server, SNMPv1/v2c/v3, HTTP/HTTPS server, TFTP client and server, ICMPv6, SNMP Client, Web Services (Print/Scan), Syslog	Spare part retention	5 year(s)



4977766823753

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.