

**Philips 2000 series 27E2N2500/00 computer monitor 68.6 cm (27")
2560 x 1440 pixels Quad HD LCD Black**

Brand : Philips

Product family: 2000 series

Product code: 27E2N2500/00

Product name : 27E2N2500/00

Monitor 27E2N2500 Quad HD monitor

Philips 2000 series 27E2N2500/00 computer monitor 68.6 cm (27") 2560 x 1440 pixels Quad HD LCD Black:

This monitor is packed with features that allow you to work with absolute precision. Its Quad HD resolution, along with a 120Hz refresh rate and 1ms MPRT, this monitor showcases detailed imagery with the utmost definition.

Philips 2000 series 27E2N2500/00. Display diagonal: 68.6 cm (27"), Display resolution: 2560 x 1440 pixels, HD type: Quad HD, Display technology: LCD, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. VESA mounting. Product colour: Black



Display		Ergonomics	
Display diagonal *	68.6 cm (27")	Panel mounting interface	100 x 100 mm
Display resolution *	2560 x 1440 pixels	Cable lock slot *	✓
HD type *	Quad HD	Cable lock slot type	Kensington
Native aspect ratio *	16:9	Height adjustment *	✗
Display technology *	LCD	Tilt adjustment	✓
Panel type *	IPS	Tilt angle range	-5 - 20°
LED backlight	✓	On Screen Display (OSD)	✓
Backlight type	W-LED		
Touchscreen *	✗		
Display brightness (typical)	300 cd/m²	On Screen Display (OSD) languages	Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish, Ukrainian
Response time *	4 ms		
Response time measurement type	GTG (Gray to Gray)		
Response time (MPRT)	1 ms		
Anti-glare screen	✓	Number of OSD languages	21
Screen shape *	Flat	Plug and Play	✓
Contrast ratio (typical) *	1500:1	LED indicators	Operation, Stand-by
Dynamic contrast ratio marketing name	Mega Infinity DCR		
Maximum refresh rate *	120 Hz	Power	
Viewing angle, horizontal	178°	Energy efficiency class (SDR) *	C
Viewing angle, vertical	178°	Energy efficiency class (HDR) *	Not available
Display number of colours *	16.7 million colours	Energy consumption (SDR) per 1000 hours *	13 kWh
Pixel pitch	0.2331 x 0.2331 mm	Power consumption (typical) *	22.97 W
Pixel density	109 ppi	Power consumption (standby) *	0.5 W
Horizontal scan range	30 - 140 kHz	Power consumption (off)	0.3 W
Vertical scan range	48 - 75 Hz	AC input voltage	100 - 240 V
Viewable size, horizontal	59.7 cm	AC input frequency	50/60 Hz
Viewable size, vertical	33.6 cm	Power supply type	External
Display diagonal (metric)	68.6 cm		

Display		Operational conditions	
High Dynamic Range (HDR) supported	✓	Operating temperature (T-T)	0 - 40 °C
High Dynamic Range (HDR) technology	High Dynamic Range 10 (HDR10)	Storage temperature (T-T)	-20 - 60 °C
DDC/CI	✓	Operating relative humidity (H-H)	20 - 80%
Haze rate	25%	Operating altitude	0 - 3658 m
Surface hardness	3H	Non-operating altitude	0 - 12192 m
Colour gamut standard	sRGB	Weight & dimensions	
Display sRGB	✓	Width (with stand)	616 mm
Display panel size	68.6 cm (27")	Depth (with stand)	200 mm
Performance		Height (with stand)	454 mm
NVIDIA G-SYNC *	✗	Weight (with stand)	3.22 kg
AMD FreeSync *	✗	Width (without stand)	616 mm
VESA Adaptive Sync support	✓	Depth (without stand)	33 mm
Flicker-free technology	✓	Height (without stand)	359 mm
Low Blue Light technology	✓	Weight (without stand)	2.85 kg
Multimedia		Packaging data	
Built-in speaker(s) *	✗	Package width	6900 mm
Built-in camera *	✗	Package depth	124 mm
Design		Package height	480 mm
Market positioning *	Home	Package weight	5.56 kg
Product colour *	Black	Sustainability	
Ports & interfaces		Doesn't contain	PVC/BFR
Built-in USB hub *	✗	Other features	
HDMI *	✓	Compatible operating systems	DDC/CI; Mac OS X; sRGB; Windows 11/10
HDMI ports quantity	1	Exterior finish type	Textured
HDMI version	2.0	User controls	Power On/Off; Menu; Brightness; Input; SmartImage
DisplayPorts quantity	1	Picture enhancement	SmartImage
DisplayPort version	1.4	Regulatory Approvals	CB; CE Mark; PSE; BSMI; UKCA; EMF; FCC; ICES-003
HDCP	✓	Adaptive synchronisation	✓
HDCP version	2.2	EasyRead mode	✓
Ergonomics		LowBlue mode	✓
VESA mounting *	✓	Compliance certificates	BSMI, CB, CE, EMF, Federal Communications Commission (FCC), ICES, PSE, RoHS, UKCA
		Mean time between failures (MTBF)	50000 h
		Recycling data	
		Recyclable packaging material	100%



8721038004472

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.