



TP-Link IES206GPP network switch Managed Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Brand : TP-Link

Product code: IES206GPP

Product name : IES206GPP

- 4× Gigabit RJ45 Ports (1× PoE++, 3× PoE+)
 - 1× Gigabit Combo RJ45/SFP Slot, 1× Gigabit SFP Slot
 - 120W Power Budget* with up to 60W for PoE++ Port
 - Professional Industrial-Grade Design: -40~75°C Operating Temperature, 6kV Lighting Protection, and 1+1 Redundant Power Input
 - Abundant Features: Up to 820ft (250m) PoE,** VLAN, QoS, and STP/RSTP
 - Centralized Cloud Management via the Web or Omada App
 - Durable IP40 Aluminum Casing and DIN-rail / Wall-mount Design
- IES206GPP Omada 6-Port Gigabit Industrial Easy Managed Switch with 3-Port PoE+ and 1-Port PoE++

TP-Link IES206GPP network switch Managed Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black:

Industrial-Grade Protection Built for Harsh Environments

Enhanced Networking Stability and Security

Easy Operation and Maintenance with Omada's Free Cloud Management



Management features		Design	
Switch type *	Managed	DIN rail mounting	✓
Ports & interfaces		Performance	
Basic switching RJ-45 Ethernet ports quantity *	4	Fanless	✓
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power	
Combo SFP ports quantity	1	Power source *	DC/PoE
SFP module slots quantity	1	Redundant power supply (RPS) support	✓
Network		DC input voltage	12 - 57 V
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1w, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3x	Power over Ethernet (PoE)	
10G support *	✗	Power over Ethernet (PoE) *	✓
Port mirroring	✓	Power over Ethernet (PoE) type supported	PoE+, PoE++ (4PPoE)
Flow control support	✓	Power over Ethernet plus (PoE+) ports quantity	3
Link aggregation	✓	Power over Ethernet 4PPoE (PoE++) ports quantity	1
Broadcast storm control	✓	Power over Ethernet (PoE) power per port	30 W
Auto MDI/MDI-X	✓	Total Power over Ethernet (PoE) budget	120 W
Spanning tree protocol	✓	Operational conditions	
Ethernet LAN data rates	10,100,1000 Mbit/s	Operating temperature (T-T)	-40 - 75 °C
Auto-negotiation	✓	Storage temperature (T-T)	-40 - 85 °C

Data transmission		Operational conditions	
Switching capacity *	12 Gbit/s	Operating relative humidity (H-H)	5 - 95%
Forwarding rate	8.93 Mpps	Storage relative humidity (H-H)	5 - 95%
MAC address table *	8000 entries	Weight & dimensions	
Store-and-forward	✓	Width	155 mm
Jumbo frames support	✓	Depth	120 mm
Jumbo frames	15000	Height	60 mm
Security		Packaging content	
DHCP features	DHCP client	Quick start guide	✓
IGMP snooping	✓	Certificates	
Multicast features		Certification	FCC, CE, RoHS
Multicast support	✓		
Design			
Rack mounting *	✓		
Product colour	Black		
Wall mountable	✓		



1210002602051



0840460600927



840460600927

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.