

DeepCool PF750 power supply unit 750 W 20+4 pin ATX ATX Black

Brand : DeepCool
Product code: R-PF750D-HA0B-EU
Product name : PF750

- OPP/OVP/SCP
 - 80 PLUS White
 - 750 W
- 750 W, ATX 12V V2.4, 80 PLUS White, 120 mm Hypro Bearing, 150×140×86 mm, black

DeepCool PF750 power supply unit 750 W 20+4 pin ATX ATX Black:

The DeepCool PF Series Power Supply Unit offers safe and stable power performance with reliable 80 PLUS Standard efficiency and affordable pricing.

TO HIGHER STANDARDS

Certified for 80 PLUS 230V EU Standard efficiency that ensures 85% efficiency under typical loading of 50%. Better efficiency translates into lower energy waste and lower temperatures for more cost savings.


SILENT HYDRAULIC BEARING FAN

Optimally balanced for low-noise performance, the 120mm fluid bearing fan improves overall life expectancy and reduces friction and vibration.

FLAT BLACK CABLES

Stealthy and flexible, the fixed flat black cables are easy to maneuver for cable management while also taking up less space in your system.

- Main Power Connector 24 (20+4)Pin x1
EPS 12V Connector 8 (4+4)Pin x2
2x PCI-E (6+2)Pin Double connector
2x SATA x3 + 4Pin Peripheral x1



Power		Performance	
Total power *	750 W	80 PLUS certification *	80 PLUS White
AC input voltage *	230 V	Purpose *	PC
Efficiency	85%	Power supply unit (PSU) form factor *	ATX
Power protection features	Over power, Over voltage, Short circuit, Under voltage	Bearing technology	Hypro Bearing
Ports & interfaces		Mean time between failures (MTBF)	100000 h
Motherboard power connector *	20+4 pin ATX	Design	
Motherboard power cable length	55 cm	Product colour	Black
Number of SATA power connectors	6	Cooling type	Active
SATA power cable length	450 mm	Fan diameter	12 cm
Peripheral (Molex) power connectors (4-pin) *	2	Number of fans	1 fan(s)
Peripheral (Molex) power cable length	900 mm	Operational conditions	
EPS power connector (4+4 pin)	✓	Operating temperature (T-T)	0 - 40 °C
ATX power connector (20+4 pin)	✓	Certificates	
Cabling type	Non-Modular	Certification	CB/CCC/CE/UKCA/EAC/RCM
		Weight & dimensions	
		Width	150 mm
		Depth	140 mm
		Height	86 mm



6933412711605

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-MAY-2026. Prints or copies of Information are only valid on the printed Publication date