Epson TM-J7200 (301) W/O MICR,BLACK,INC PSU,EU



Brand : Epson

Product code: C31CF69301

Product name : Epson TM-J7200 (301) W/O MICR,BLACK,INC PSU,EU

- Versatile inkjet POS printer: Faster, better quality and more versatile
- Low TCO: Similar overall costs to previous dot matrix model
- Durable prints: Print is now more resistant to water and light
- Simple maintenance: Ink and paper rolls are very easy to replace
- Backwards compatible: Crisp, clear text and glossy photos

TM-J7200 (301) W/O MICR,BLACK,INC PSU,EU

Epson TM-J7200 (301) W/O MICR,BLACK,INC PSU,EU. Print technology: Inkjet, Type: POS printer, Print speed: 98 mm/sec. Supported paper width: 58 - 83 mm, Media thickness: 0.06 - 0.09 mm, Maximum paper size (slip): 230 x 297 mm. Connectivity technology: Wired, USB connector: USB Type-B, Interface: USB 2.0, Ethernet interface (100 Base-TX / 10 Base-T), Drawer kick-out, Customer Display. Sound pressure level (printing): 55 dB, Mean time between failures (MTBF): 180000 h, Autocutter durability: 1.5 million cuts. Product colour: Black



Printing	
Colour	✗
Print speed	98 mm/sec
Print speed (graphic)	98 mm/sec
Print speed (receipt)	98 mm/sec
Print speed (slip)	85 mm/sec
Printing characters	Text, Graphic, Barcode
Character sets	ANK
Alphanumeric memory	95
Print technology *	Inkjet
Type *	POS printer

Paper handling	
Supported paper width	58 - 83 mm
Media thickness	0.06 - 0.09 mm
Maximum paper size (slip)	230 x 297 mm

Ports & interfaces	
USB port *	✓
USB 2.0 ports quantity	1
USB connector	USB Type-B
Connectivity technology *	Wired
Ethernet LAN (RJ-45) ports	1
Interface	USB 2.0, Ethernet interface (100 Base-TX / 10 Base-T), Drawer kick-out, Customer Display

Network	
Ethernet LAN *	✓
Wi-Fi *	✗

Features	
Sound pressure level (printing)	55 dB
Mean time between failures (MTBF)	180000 h
Half-cutter	✗
Autocutter durability	1.5 million cuts
Country of origin	Indonesia
Printer receipt unit life	3700000000 lines
Printer slip unit life	5000000 lines

Operational conditions	
Operating temperature (T-T)	10 - 35 °C
Storage temperature (T-T)	-20 - 40 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	20 - 85%

Weight & dimensions	
Width	195 mm
Depth	260 mm
Height	188 mm
Weight	5.1 kg

Packaging data	
Cables included	AC
Quantity per pack	1 pc(s)
Package width	297 mm
Package depth	390 mm
Package height	305 mm
Package weight	7.2 kg

Logistics data	
Pallet weight (UK)	0 g
Harmonized System (HS) code	84433210
Products per pallet	48 pc(s)
Products per pallet layer	8 pc(s)
Pallet gross width	80 cm
Pallet gross length	120 cm
Pallet gross height	171 cm
Pallet gross weight	0 g
Products per pallet (UK)	60 pc(s)
Products per pallet layer (UK)	10 pc(s)
Pallet width (UK)	100 cm
Pallet length (UK)	120 cm
Pallet height (UK)	171 cm

Technical details	
Font styles	ANK

Features	
Safety	TÜV, TÜV (EN60950-1)
Certification	CE, EN55024, EN55032 Class A, IEC61000-4-2, IEC61000-4-3, IEC61000-4-4, IEC61000-4-5, IEC61000-4-6, IEC61000-4-11

Design	
Product colour *	Black

Power	
Power source type *	DC
AC input voltage	24 V
Power consumption (standby)	70000 mA

Technical details	
Box contents	CD Manual, Ink Cartridge, PS-180, Power cable, Power switch cover, Roll paper, Setup guide, USB cable, User manual (CD)
Voltage	24 V
Safety warning	Contains 2,4,7,9-tetramethyldec-5-yne-4,7-diol. May produce an allergic reaction. Always follow the information on the product label.

Other features	
Paper dimensions	58 mm - 83 mm
Mean cycles between failures (MCBF)	5000000

8715946639031

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 14-NOV-2026. Prints or copies of Information are only valid on the printed Publication date