



FSP FlexGURU Pro 500W Power supply unit FLEX ATX ATX2.52 / Flex ATX1.23 Black



Brand : FSP

Product code: PPA5008401

Product name : FlexGURU Pro 500W Power supply unit
FLEX ATX ATX2.52 / Flex ATX1.23 Black

- Compliance with newest Flex ATX V1.22
- Efficiency $\geq 90\%$ at typical load
- 80 PLUS Gold Certification
- Intelligent fan speed control
- Quiet and long-lasting 40mm dual ball bearing fan
- Black round cables for the need of enthusiasts
- Powerful single +12V rail design
- Main Japanese electrolytic capacitors
- Intel Latest CPU ready
- Full protections OCP,OVP, SCP,OPP,OTP

FlexGURU PRO 500W

FSP FlexGURU Pro 500W Power supply unit FLEX ATX ATX2.52 / Flex ATX1.23 Black. Total power: 500 W, AC input voltage: 100 - 240 V, AC input frequency: 50 - 60 Hz. Motherboard power connector: 24-pin ATX, Cabling type: Non-Modular. Purpose: NAS/storage server, Power supply unit (PSU) form factor: 1U, 80 PLUS certification: 80 PLUS Gold. Product colour: Black, Cooling type: Active, Fan diameter: 4 cm. Cables included: CPU, PCIe, Peripheral (Molex), SATA

Power		Ports & interfaces	
Total power *	500 W	PCI Express power connectors (6+2 pin)	2
AC input voltage *	100 - 240 V	CPU power connector (4+4 pin)	✓
AC input frequency	50 - 60 Hz	ATX Power connector (24-pin)	✓
Input current	8-4 A	Floppy drive power connector	1
Power Factor Correction (PFC) type	Active	Floppy disk drive connector	✓
Combined power (+3.3V)	90 W	Cabling type	Non-Modular
Combined power (+5V)	90 W	Performance	
Max output current (+3.3V)	14 A	80 PLUS certification *	80 PLUS Gold
Max output current (+12V)	41 A	Purpose *	NAS/storage server
Max output current (+5V)	16 A	Power supply unit (PSU) form factor *	1U
Max output current (-12V)	0.3 A	Bearing technology	Ball bearing
Max output current (+5Vsb)	3 A	Design	
Efficiency	90%	Product colour	Black
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit	Cooling type	Active
Ports & interfaces		Fan diameter	4 cm
Motherboard power connector *	24-pin ATX	Number of fans	1 fan(s)
Number of SATA power connectors	4	Packaging content	
Peripheral (Molex) power connectors (4-pin) *	2	Cables included	CPU, PCIe, Peripheral (Molex), SATA
EPS power connector (8-pin)	✓	Weight & dimensions	
		Width	40.5 mm
		Depth	150 mm
		Height	81.5 mm



4713224522925

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.