



Lindy 1m Cat.5e U/UTP Network Cable, Grey

Brand : Lindy

Product code: 48362

Product name : 1m Cat.5e U/UTP Network Cable, Grey

1m Cat.5e U/UTP Network Cable, Grey


Lindy 1m Cat.5e U/UTP Network Cable, Grey:

Cat.5e U/UTP PVC network cable with support for bandwidth up to 100MHz and features a snagless design with gold plated contacts for ethernet standards up to 1GBase-T.

Cat.5e cable, designed for operating frequencies up to 100MHz. The unshielded version (U/UTP) is designed in its electrophysical parameters (NExT, FExT etc.) in such a way that it can be used for Gigabit Ethernet despite the lack of shielding. These cables are manufactured and tested according to the ISO/IEC 11801 specification. The cables are packaged individually in a polybag.

The gold-plated contacts ensure reliable, corrosion-free connections over extensive periods of time. A robust snagless strain relief design prevents damage to the connector latch during installation and removal.

Available lengths: 0.3m, 0.5m, 1m, 1.5m, 2m, 3m, 5m, 7.5m, 10m, 15m, 20m, 30m, 40m, 50m, 60m, 70m, 80m, 90m, 100m.



Features		Features	
Product colour *	Grey	Bend radius (min)	5.7 cm
Cable length *	1 m	Molded cable boot	✓
Cable standard *	Cat5e	Operational conditions	
Cable shielding *	U/UTP (UTP)	Operating temperature (T-T)	-10 - 60 °C
Connector 1 *	RJ-45	Storage temperature (T-T)	-20 - 75 °C
Connector 2 *	RJ-45	Certificates	
Connector 1 gender *	Male	Certification	RoHS, REACH, UL, California Proposition 65
Connector 2 gender *	Male	Weight & dimensions	
Connector contacts plating	Gold	Outer diameter	4.8 mm
Jacket material	Polyvinyl chloride (PVC)	Connector 1 dimensions (WxDxH)	11.6 x 22.8 x 8.3 mm
Conductor type	Stranded	Connector 2 dimensions (WxDxH)	11.6 x 22.8 x 8.3 mm
Conductor material	Copper	Packaging data	
Cable type	Straight-through cable	Package type	Polybag
Cabling technology	10/100/1000Base-T(X)	Logistics data	
AWG wire size	26	Harmonized System (HS) code	84733080
Data transfer rate	1000 Mbit/s		
Frequency	100 MHz		



4002888483629

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.