

Zalman ZM650-GVII power supply unit 650 W 20+4 pin ATX ATX Black

Brand : Zalman

Product code: ZM650-GVII

Product name : ZM650-GVII



- Active PFC with up to 99.5% maximum power factor
- 12V DC-TO-DC converter with 99% availability
- System standby power at 0.5W or less
- Built-in EMI filter for noise reduction
- 105°C capacitor
- 120mm fan with FDB Bearing
- ErP Lot 6 Certified

Zalman ZM650-GVII power supply unit



[Zalman ZM650-GVII power supply unit 650 W 20+4 pin ATX ATX Black:](#)

80 Plus Bronze 230V EU certified Power Supply Unit. It supplies smooth power to the PC while reducing unnecessary power consumption by using high-performance parts that are very durable and reliable. Zalman ZM650-GVII. Total power: 650 W, AC input voltage: 200 - 240 V, AC input frequency: 50 - 60 Hz. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 55 cm, SATA power cable length: 400 mm. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Bronze. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Cables included: AC, CPU, PCIe, Peripheral (Molex), SATA

Power		Performance	
Total power *	650 W	Supported motherboard form factors	ATX, micro ATX, Mini-ATX
AC input voltage *	200 - 240 V	Purpose *	PC
AC input frequency	50 - 60 Hz	Power supply unit (PSU) form factor *	ATX
Input current	6 A	Noise level	36.3 dB
Power factor	99	Bearing technology	FDB
Power Factor Correction (PFC) type	Active	Mean time between failures (MTBF)	100000 h
Combined power (+3.3V)	110 W	Design	
Combined power (+12V)	648 W	Product colour	Black
Combined power (+5V)	110 W	Cooling type	Active
Combined power (-12V)	3.6 W	Fan diameter	12 cm
Combined power (+5Vsb)	12.5 W	Number of fans	1 fan(s)
Max output current (+3.3V)	20 A	Fan location	Top
Max output current (+12V)	54 A	On/off switch	✓
Max output current (+5V)	18 A	Operational conditions	
Max output current (-12V)	0.3 A	Operating temperature (T-T)	0 - 40 °C
Max output current (+5Vsb)	2.5 A	Storage temperature (T-T)	-40 - 70 °C
Efficiency	88%	Operating relative humidity (H-H)	5 - 85%
Power protection features	Over current, Over power, Over voltage, Short circuit, Under voltage	Storage relative humidity (H-H)	5 - 95%
Ports & interfaces		Packaging content	
Motherboard power connector *	20+4 pin ATX	Cables included	AC, CPU, PCIe, Peripheral (Molex), SATA
Motherboard power cable length	55 cm	Certificates	
Number of SATA power connectors	2	Compliance certificates	RoHS
SATA power cable length	400 mm	Certification	80 Plus, CB, CE, KC, EAC, RoHS
Peripheral (Molex) power connectors (4-pin) *	1		
Peripheral (Molex) power cable length	400 mm		
PCI Express power connectors (6+2 pin)	2		

Ports & interfaces		Safety regulation & standards	
PCI Express power cable length	50 cm	Safety	CB, CE, KC, EAC, RoHS
CPU power connector (4+4 pin)	✓	Weight & dimensions	
CPU power cable length	65 cm	Width	140 mm
ATX power connector (20+4 pin)	✓	Depth	150 mm
PCI Express connector	✓	Height	86 mm
Cabling type	Non-Modular	Weight	2.01 kg
Performance		Packaging data	
80 PLUS certification *	80 PLUS Bronze	Package width	180 mm
		Package depth	280 mm
		Package height	100 mm
		Package weight	2.05 kg
		Package type	Box
		Logistics data	
		Country of origin	China



8809213769603

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-APR-2026. Prints or copies of Information are only valid on the printed Publication date